

5092 Aber Road Williamsburg, Ohio 45176 513/724-6114

December 10, 2015

Mr. David Petrovsky United States Environmental Protection Agency Region 5, Attn: DRE-9J 77 West Jackson Boulevard Chicago, IL 60604-3590

RE: Administrative Order on Consent, O&M Progress Report No. 39 CECOS International, Inc. Docket No. V-W-024-94 EPA I.D. No. OHD 087 433 744

Dear Mr. Petrovsky:

As required by Section VIII.E and XIV. 6 of the above referenced Consent Order, CECOS International, Inc. (CECOS) is submitting to Region 5 of the United States Environmental Protection Agency (U.S. EPA) the O&M Progress Report for the period of June 2015 through November 2015. This progress report has been formatted to conform to the requirements of Attachment A to the Consent Order and is being submitted on a semiannual basis as requested in U.S. EPA's August 4, 1998 letter approving the CMI CC Report.

- 1. Description of CMI O&M Activities Completed:
 - A. General O&M Activity:

During the months of June 2015 through November 2015, CECOS operated the CMI area leachate pumps in accordance with the CMI O&M Manual. The CMI groundwater gradient control pumps were not operated this period in accordance with the approval from U.S. EPA to shut down the gradient control system dated March 31, 2009.

B. Leachate/Groundwater Pumping:





During the six-month period covered by this report, 42,000 gallons of leachate were pumped from the CMI area. No CMI groundwater was pumped or shipped off-site for disposal. A total of 40,000 gallons of CMI leachate was shipped directly off-site for disposal. An additional volume of purge water generated from the sampling of the underdrains and CMI wells was combined with the CMI leachate since the groundwater gradient control system has been shutdown.

At the Leachate Treatment System (LTS), 140,828 gallons of leachate influent was added to the system this period. A total of 151,760 gallons of LTS effluent were produced along with 1,210 gallons of solids. A total of 140,000 gallons of treated leachate were shipped off site during the period. The primary source of the leachate treated at the LTS was 119,822 gallons of leachate that was pumped from the closed RCRA disposal units to the Leachate Accumulation Points (LAPs) from June 2015 through November 2015. A total of 120,640 gallons of leachate was transferred from the LAPs to the LTS. A summary of the leachate and groundwater pumping for the period is included as Exhibit No. 1. Another 20,217 gallons of leachate was pumped during the period using the vacuum truck from sumps, discharge lines, side risers, and other miscellaneous locations.

C. Groundwater Monitoring:

A CMI Post Shutdown Monitoring Event was conducted in October 2015. Sampling of wells both inside and outside of the slurry wall was scheduled for the COI/TCL parameter list.

D. Reports and Other Submissions:

The 38th O&M Progress Report for CMI operations at Aber Road was submitted to U.S. EPA by June 10, 2015.

2. Summary of Findings:

Data validation was performed this period on groundwater samples collected during the April 2015 CMI monitoring event. In April 2015, no COI compounds were confirmed detected at any sampling location outside the slurry wall. Wells outside the slurry wall were analyzed in April 2015 for the applicable VOC compounds on the COI list. One well located inside the slurry wall (MP-246) was sampled in April 2015. MP-246 had 4 COI compounds detected that exceeded the



CMI Cleanup Standard. The data validation summary report for the April 2015 monitoring event is included in this report in Exhibit No. 4.

	monitoring event is included in this report in Exhibit No. 4.
3.	Summary of CMI Changes:
	None.
4.	Summary of Contacts:
	None.
5.	Summary of Problems:
	None.
6.	Actions to Rectify Problems:
	None.
7.	Changes in Key Project Personnel:
	None.
8.	Projected Work for Next Period:
183	A. Continue leachate and groundwater management activities as required.
	B. Continue CMI operations and maintenance as required.
	C. Perform CMI Performance Monitoring in April 2016.





- 9. Copies of Reports, Data, Etc.:
 - A. A summary of leachate management activities, including volumes of leachate pumped, treated, and shipped off-site is included in Exhibit No. 1.
 - B. A summary of groundwater head levels across the slurry wall for October 2015 are included in Exhibit No. 2. While the groundwater gradient control wells are shut down, the performance standard for groundwater gradient levels across the slurry wall does not apply.
 - C. regarding methane monitoring, leachate Information gas measurements and leachate pumping activity at the Sanitary Landfill is included in Exhibit No. 3. Recent analytical reports for monitoring well MP-290B are also included in Exhibit No. 3. The only COI compounds detected above the reporting limit in well MP-290B were chloroethane and cis-1,2dichloroethene. Both compounds were found at levels well below their respective Cleanup Standard listed in the CMI O&M Manual during the July and October 2015 sampling events. No "J" values for any VOC were reported in the July or October 2015 results. All other VOC compounds were reported to be not detected (ND).
 - D. A data validation report prepared by SCS Engineers for the April 2015 CMI sampling event is presented in Exhibit No. 4.
 - E. The report entitled "Exhibit 5 Corrective Measures Implementation Performance Monitoring Evaluation" prepared by Eagon & Associates is included as Exhibit No. 5. This report includes an evaluation of the October 2015 groundwater data with comparisons to the groundwater cleanup standards and concentration-based performance standards (CBPS) and Screening Levels in the revised CMI O&M Manual.

10. Other items.

A. A field sampling audit was performed by Matthew Barnett of The Mannik & Smith Group, Inc. in October 2015 for the groundwater sampling activities in the Aber Road CMI area. The audit was performed as described in the QAPjP. A copy of the audit report is included as Exhibit No. 6.





- B. An audit was performed of the Aber Road Contract Laboratory for their analysis of the October 2015 event groundwater samples. The audit was performed by Trillium, Inc. and included a review of Performance Evaluation (PE) samples that were submitted to the lab for blind analysis. A copy of the report is included as Exhibit No. 7.
- C. Organic vapor pressure testing of the Aber Road leachate treatment system influent was performed in July 2015. A copy of the test report is included as Exhibit No. 8. The result of the analysis was a leachate organic vapor pressure of 0.027 psi, well below the rule applicability threshold level in 40CFR 60, Subpart Kb of 3.5 kPa (0.508 psi). The duplicate sample had a result of 0.021 psi, also below the applicable regulatory threshold listed in Subpart Kb.

If you have any questions or comments, please feel free to contact the Aber Road facility at (513) 724-6114.

Sincerely:

CECOS International, Inc.

Daniel Deborde

Project Coordinator

CY: J. Lee, USEPA Region 5

S. Rabolt, Clermont County

M. Gibson, Eagon & Associates

G. Saylor, SCS Engineers

T. Hull, Ohio EPA SWDO

File M.3.3





DOCUMENT CERTIFICATION

DOCUMENT NAME: O&M PROGRESS REPORT No. 39

"I certify that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to evaluate the information submitted. I certify that the information contained in or accompanying this submittal is true, accurate, and complete. As to those identified portion(s) of this submittal for which I cannot personally verify the accuracy, I certify that this submittal and all attachments were prepared in accordance with procedures designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those directly responsible for gathering the information, or the immediate supervisor of such person(s), the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

Signature:

Name:


Daniel Deborde

Title:

Project Coordinator

Date:

December 10, 2015



CMI Semi-Annual O&M Report

Leachate/Groundwater Volumes (Gallons)

CMI Leachate/Groundwater Summary

Month	Leachate Pumped	Transferred	GW Pumped	GW Shipped Offsite
Jun-15	4,022	5,000	0	0
Jul-15	11,843	10,000	0	0
Aug-15	5,414	5,000	0	0
Sep-15	4,586	5,000	0	0
Oct-15	10,485	10,000	0	0
Nov-15	5,650	5,000	0	0
Total	42,000	40,000	0	0

Leachate Treatment (LTS) Summary

Month	LTS Influent	LTS Effluent	Solids Produced	Leachate Shipped
Jun-15	27,527	29,576	110	20,000
Jul-15	31,049	32,770	55	30,000
Aug-15	20,200	21,668	385	35,000
Sep-15	17,527	18,906	220	20,000
Oct-15	28,125	30,679	220	10,000
Nov-15	16,400	18,161	220	25,000

Total 140,828 151,760 1,210 140,000

CMI Semi-Annual O&M Report

Leachate/Groundwater Volumes

(Gallons)

Leachate Accumulation Point (LAP) Summary

$\mathbf{June}\ 2015$

Tank	Leachate Pumped	Transfer to LTS	Standpipes
T-104	1,061	1,475	L-25, 26, 27
T-105	8,205	11,800	L-34, 35, 36
T-108	2,411	3,400	L-20, 21/22, 23/24
T-109	1,510	2,725	L-15, 18, 19
T-110	1,445	2,050	L-16, 17
T-111	1,745	2,100	L-5, 6, 11, 14
T-112	3.823	5.100	L-3, 4, 7, 8, 9, 10, 12, 13

Total

20,200

28,650

July 2015

Tank	Leachate Pumped	Transfer to LTS	Standpipes
T-104	1,264	525	L-25, 26, 27
T-105	8,725	4,000	L-34, 35, 36
T-108	4,180	3,325	L-20, 21/22, 23/24
T-109	3,042	2,600	L-15, 18, 19
T-110	1,210	1,100	L-16, 17
T-111	2,342	2,100	L-5, 6, 11, 14
T-112	5,502	4,400	L-3, 4, 7, 8, 9, 10, 12, 13

Total

26,265

18,050

August 2015

Tank	Leachate Pumped	Transfer to LTS	Standpipes
T-104	1,734	1,975	L-25, 26, 27
T-105	12,832	13,450	L-34, 35, 36
T-108	3,898	3,625	L-20, 21/22, 23/24
T-109	1,685	1,700	L-15, 18, 19
T-110	905	875	L-16, 17
T-111	2,083	1,875	L-5, 6, 11, 14
T-112	4,885	4,625	L-3, 4, 7, 8, 9, 10, 12, 13

Total

28,022

28,125

September 2015

Tank	Leachate Pumped	Transfer to LTS	Standpipes
T-104	348	575	L-25, 26, 27
T-105	3,882	5,650	L-34, 35, 36
T-108	1,124	1,600	L-20, 21/22, 23/24
T-109	626	775	L-15, 18, 19
T-110	354	400	L-16, 17
T-111	469	700	L-5, 6, 11, 14
T-112	1,999	2,550	L-3, 4, 7, 8, 9, 10, 12, 13

Total

8,802

12,250

October 2015

Tank	Leachate Pumped	Transfer to LTS	Standpipes
T-104	1,052	1,255	L-25, 26, 27
T-105	8,107	8,600	L-34, 35, 36
T-108	2,120	625	L-20, 21/22, 23/24
T-109	1,140	1,300	L-15, 18, 19
T-110	629	750	L-16, 17
T -111	1,461	1,450	L-5, 6, 11, 14
T-112	3,676	3,800	L-3, 4, 7, 8, 9, 10, 12, 13

Total

18,185

17,780

November 2015

Tank	Leachate Pumped	Transfer to LTS	Standpipes
T-104	1,015	670	L-25, 26, 27
T-105	7,412	5,975	L-34, 35, 36
T-108	2,810	3,725	L-20, 21/22, 23/24
T-109	1,104	815	L-15, 18, 19
T-110	661	350	L-16, 17
T-111	1,521	1,250	L-5, 6, 11, 14
T-112	3,825	3,000	L-3, 4, 7, 8, 9, 10, 12, 13

Total

18,348

15,785

EXHIBIT NO. 2

OCTOBER 2015 GRADIENT ANALYSIS CECOS INTERNATIONAL, INC. ABER ROAD FACILITY

		Nested Pair	Inside/Outside	Top of Casing Elevation	Depth to Water	Ground-Water Elevation	Elevation Differential
Location	Zone	Number	Slurry Wall	(ft., MSL)	(ft.)	(ft., MSL)	(ft.)
USPZ-1	US	1	Inside	908.00	7.61	900.39	-2.00
MP-303B	US		Outside	906.24	7.85	898.39	
880PZ-1	880	2	Inside	908.49	8.30	900.19	-3,00
MP-208	880	·	Outside	907.57	10.38	897.19	
880PZ-2	880	3	Inside	907.11	6.13	900.98	4.00
MP-305A	880		Outside	908.11	3.13	904.98	
880PZ-3	880	4	Inside	915.45	9.63	905.82	0.61
MP-238AR	880		Outside	916.36	9.93	906.43	
880PZ-4	880	5	Inside	909.45	6.59	902.86	-1.52
MP-304A	880		Outside	908.42	7.08	901.34	
880PZ-5	880	6	Inside	914.42	9.77	904.65	-4.60
MP-241AR	880		Outside	916.39	16.34	900.05	

Notes:

A positive differential indicates an inward gradient

 $US=Upper\ Sand\ Zone$

880=880 Sand Zone

Water Levels Measured October 12, 2015

EXHIBIT NO. 3

LEACHATE HEAD LEVELS June 2015

	T*************************************		June 2015		
WELL	DATE: 06/03/15	DATE: 6/9/15	DATE: 6/16/15	DATE: 6/23/15	DATE: 6/29/15
1	1.8	1.8	1.8	1.8	1.7
2	2.0	12.2/2.0 A	1.2	2.0	1.8
3	Abandoned	Abandoned	Abandoned	Abandoned	Abandoned
4	1.9	2.0	1.8	1.6	1.9
5	2.2	2.2	2.0	1.8	2.1
6	1.6	1.7	1.5	1.5	1.6
7	2.1	2.1	1.8	1.8	2.1
8	1.0	0.9	1.5	1.5	1.0
9	1.5	1.6	1.9	2.0	1.5
10	1.3	1.4	1.7	2.2	1.7
11	2.1	1.6	1.4	1.5	2.1
12	1.1	1.1	1.1	1.1	1,1
13	1.6	2.1	1.5	1.5	17
14	1.7	1.6	1.7	1.7	1.6
15	1.7	1.9	1.8	1.9	1.6
16	1.5	2.1	2.0	1.7	2.1
17	1.4	1.5	1.8	1.7	1.4
18	1.9	1.9	1.9	1.8	1.8
19	2.0	2.5/1.7 A	2.0	1.5	1.5
20	5.9/1.2 A	8.9/1.8 A	1.6	1.6	1.2
21	1.7	1.8	2.0	1.6	1.9
22	1.5	1.6	1.5	1.6	1.5
23	1.5	1.6	1.4	1.4	1.4
24	1.4	1.5	1.3	1.3	1.4
1B	1.6	1.9	1.5	1.5	2.0
2B	1.9	5.9/2.1 A	5.7/1.7 A	2.1	1.7

Strength of the control of

MEMORANDUM

TO:

Dan Deborde

FROM:

Doug Kattwinkel

SUBJECT:

Sanitary Landfill System Report for the Month of June 2015

DATE:

July 2, 2015

Gas System Operation

The system was operational 1* day out of a possible 30 days. The system operated a total 3 hours for the month out of a possible 720 hours. The gas system operation averages for the month of June are 25% methane and 839°F flare temperature. *Approximate runtime flare down frequently due to low gas production.

- 1. Explosive Gas Monitoring System: Gas monitoring for the semi-annual was completed May 28, 2015.
- 2. Gas Wells: The gas wells are functioning correctly with regular pumping of condensate drains.
- 3. Header Lines: The header lines are functioning correctly.
- 4. Condensate Drains: All the condensate drains (CD) are working properly.
- 5. Knock Out Pot: The knock out pot remained dry the entire month.
- 6. Blower: The blower is functioning correctly.
- 7. Electric Controls: All electric controls are working properly.
- 8. Flare Assembly: The flare assembly is working correctly.

Cap Maintenance

Landfill cap in good condition.

Sanitary Leachate Collection System

The sanitary landfill dewatering system was operational all days during the month of June. The monthly summary for leachate levels are attached for your review.

A total of 42,000 gallons of sanitary leachate was shipped off site for disposal during the month of June. All 42,000 gallons were disposed at the Lower East Fork WWTP. All leachate wells are functioning. The leachate head levels remain below the approved alternate levels.

DK/dd

Cy: File (H.6)

LEACHATE HEAD LEVELS July 2015

The state of the s	andy and an one particular special and a second special specia	and the state of t	The state of the s		
WELL	DATE: 07/10/15	DATE: 07/14/15	DATE: 07/15/14	DATE: 07/22/15	DATE: 07/28/15
11	1.7	1.7	1.8	2.0	1.9
2	1.8	8.6/1.6 A	1.1	15.2/1.2 A	2.2
3	Abandoned	Abandoned	Abandoned	Abandoned	Abandoned
4	1.8	1.9	1.9	1.9	1.9
5	2.0	2.2	2.2	2.2	2.2
6	1.6	1.6	1.5	1.6	1.6
7	2.1	2.1	2.0	2.1	2.1
- 8	1.0	1.0	1.2	1.0	1.0
9	1.5	1.5	1.4	1.5	1.5
10	1.6	1.4	1.3	1.4	1.7
11	2.1	1.8	1.9	2.0	2.1
12	1.1	1,1	1.1	1.0	1.1
13	1.6	2.1	9.1/1.5 A	11.1/1.5 A	1.5
14	1.3	1.3	1.7	2.0	1.9
15	1.7	1.7	1.7	1.6	1.4
16	1.5	1.8	2.0	2.2	2.0
17	1.4	1.6	1.5	1.6	1.5
18	1.8	1.8	1.8	1.9	2.1
19	1.5	2.0	1.5	1.5	1.5
20	4.9/1.6 A	1.1	5.0/1.6 A	9.6/1.2 B	3.4/1.6 A
21	2.0	11.3/1.7 B	1.7	1.5	2.0
2 2	1.5	1.7	1.5	1.5	1.6
23	1.5	1.5	1,5	1.5	1.5
24	1,4	1.4	1.4	1.4	1.4
1B	1.4	2.0	1.5	1.5	1.8
2B	1.7	1.8	1.7	1.8	1.7

A - Reset Coyote B - Installed New Pump

MEMORANDUM

TO:

Dan Deborde

FROM:

Doug Kattwinkel

SUBJECT:

Sanitary Landfill System Report for the Month of July 2015

DATE:

July 31, 2015

Gas System Operation

The system was operational 1* day out of a possible 31 days. The system operated a total 1.5 hours for the month out of a possible 744 hours. The gas system operation averages for the month of July are 25.3% methane and 957°F flare temperature. *Approximate runtime flare down frequently due to low gas production.

- 1. Explosive Gas Monitoring System: Gas monitoring for the semi-annual was completed May 28, 2015.
- 2. Gas Wells: The gas wells are functioning correctly with regular pumping of condensate drains.
- 3. Header Lines: The header lines are functioning correctly.
- 4. Condensate Drains: All the condensate drains (CD) are working properly.
- 5. Knock Out Pot: The knock out pot remained dry the entire month.
- 6. Blower: The blower is functioning correctly.
- 7. Electric Controls: All electric controls are working properly.
- 8. Flare Assembly: The flare assembly is working correctly.

Cap Maintenance

Landfill cap in good condition.

Sanitary Leachate Collection System

The sanitary landfill dewatering system was operational all days during the month of July. The monthly summary for leachate levels are attached for your review.

A total of 150,000 gallons of sanitary leachate was shipped off site for disposal during the month of July. All 150,000 gallons were disposed at the Lower East Fork WWTP. All leachate wells are functioning. The leachate head levels remain below the approved alternate levels.

DK/dd

Cy: File (H.6)

LEACHATE HEAD LEVELS August 2015

F	T	August 20	7	
WELL	DATE: 08/4/15	DATE: 08/11/15	DATE: 08/18/15	DATE: 08/25/15
1	1.8	1.8	1.9	1.8
2	1.2	1.9	1.6	1.6
3	Abandoned	Abandoned	Abandoned	Abandoned
4	1.9	1.9	1.9	1.7
5	2.2	2,1	2.2	1.8
6	1.6	1.6	1.6	1.5
7	2.1	2.0	2.1	1.8
8	1.0	1.0	1.0	1.0
9	1.5	1.5	1.5	1.5
10	1.7	1.6	1.7	1.7
11	2.1	1.9	2.0	1.7
12	1.1	1.1	1.1	1.1
13	1.6	1.5	1.5	1.5
14	1.8	1.7	1.7	1.6
15	1.7	1.8	1.8	1.8
16	2.1	2.0	1.7	1.7
17	1.5	1.6	1.5	1.4
18	2.0	2.1	2.0	1.8
19	1.5	1.5	1,5	1.5
20	3.4/1.2 A	3,3/1.4 A	1.9	1.9
21	1.8	1.9	1.7	1.5
22	1.6	1.6	1.4	1.4
23	1.5	1.5	1,4	1.4
24	1.5	1.4	1.6	1.3
1B	1.9	1.5	1.5	1.5
2B	1.7	1.7	1.8	1.7

MEMORANDUM

TO:

Dan Deborde

FROM:

Doug Kattwinkel

SUBJECT:

Sanitary Landfill System Report for the Month of August 2015

DATE:

August 31, 2015

Gas System Operation

The system was operational 1* day out of a possible 31 days. The system operated a total 2 hours for the month out of a possible 744 hours. The gas system operation averages for the month of August are 13.5% methane and 1260°F flare temperature. *Approximate runtime flare down frequently due to low gas production.

- 1. Explosive Gas Monitoring System: Gas monitoring for the semi-annual was completed May 28, 2015.
- 2. Gas Wells: The gas wells are functioning correctly with regular pumping of condensate drains.
- 3. Header Lines: The header lines are functioning correctly.
- 4. Condensate Drains: All the condensate drains (CD) are working properly.
- 5. Knock Out Pot: The knock out pot remained dry the entire month.
- 6. Blower: The blower is functioning correctly.
- 7. Electric Controls: All electric controls are working properly.
- 8. Flare Assembly: The flare assembly is working correctly.

Cap Maintenance

Landfill cap in good condition.

Sanitary Leachate Collection System

The sanitary landfill dewatering system was operational all days during the month of August. The monthly summary for leachate levels are attached for your review.

A total of 60,000 gallons of sanitary leachate was shipped off site for disposal during the month of August. All 60,000 gallons were disposed at the Lower East Fork WWTP. All leachate wells are functioning. The leachate head levels remain below the approved alternate levels.

DK/dd

Cy: File (H.6)

LEACHATE HEAD LEVELS September 2015

	September 2015					
WELL	DATE: 09/01/15	DATE: 09/08/15	DATE: 09/15/15	DATE: 09/23/15		
1	1.9	1.9	1.8	1.6		
2	1.7	1.2	1.7	1.7		
3	Abandoned	Abandoned	Abandoned	Abandoned		
4	1.9	1.9	1.9	1.8		
5	2.1	2.1_	2.1	1.9		
6	1.6	1.6	1.6	1.5		
7	2.1	2.0	2.0	1.7		
8	1.0	1.0	1.0	1.1		
9	1.4	1.5	1.5	1.5		
10	1.6	1.5	1.5	1.7		
11	1.9	1.8	2.0	1.7		
12	1,0	1.1	1.1	1.1		
13	1.6	1.6	1.6	1.5		
14	1.6	1.6	1.5	1.5		
15	1.5	2.0	1.7	1.7		
16	2.0	2.0	1.9	1.7		
17	1.5	1.5	1.5	1.5		
18	1.9	1.8	2.0	1.9		
19	1.8	1.5	1.5	1.5		
20	1.2	1.5	1.5	1.5		
21	1.4	1.6	1.6	1.6		
22	1.5	1.5	1.5	1.5		
23	1.5	1.5	1.5	1.5		
24	1.5	1.5	1.5	1.5		
1B	1.4	1.4	1.3	1.3		
2B	1.7	1.7	1.8	1.7		

MEMORANDUM

TO:

Dan Deborde

FROM:

Doug Kattwinkel

SUBJECT:

Sanitary Landfill System Report for the Month of September 2015

DATE:

September 30, 2015

Gas System Operation

The system was operational 1* day out of a possible 30 days. The system operated a total 1.5 hours for the month out of a possible 720 hours. The gas system operation averages for the month September are 23.6% methane and 850°F flare temperature. *Approximate runtime flare down frequently due to low gas production.

- 1. Explosive Gas Monitoring System: Gas monitoring for the semi-annual was completed May 28, 2015.
- 2. Gas Wells: The gas wells are functioning correctly with regular pumping of condensate drains.
- Header Lines: The header lines are functioning correctly.
- 4. Condensate Drains: All the condensate drains (CD) are working properly.
- 5. Knock Out Pot: The knock out pot remained dry the entire month.
- 6. Blower: The blower is functioning correctly.
- 7. Electric Controls: All electric controls are working properly.
- 8. Flare Assembly: The flare assembly is working correctly.

Cap Maintenance

Landfill cap in good condition.

Sanitary Leachate Collection System

The sanitary landfill dewatering system was operational all days during the month of August. The monthly summary for leachate levels are attached for your review.

A total of 24,000 gallons of sanitary leachate was shipped off site for disposal during the month of September. All 24,000 gallons were disposed at the Lower East Fork WWTP. All leachate wells are functioning. The leachate head levels remain below the approved alternate levels.

DK/dd

Cy: File (H.6)

MEMORANDUM

TO:

Dan Deborde

FROM:

Doug Kattwinkel

SUBJECT:

Sanitary Landfill System Report for the Month of October 2015

DATE:

October 31, 2015

Gas System Operation

The system was operational 1* day out of a possible 31 days. The system operated a total 1.5 hours for the month out of a possible 744 hours. The gas system operation averages for the month October are 11.85% methane and 659°F flare temperature. *Approximate runtime flare down frequently due to low gas production.

- 1. Explosive Gas Monitoring System: Gas monitoring for the semi-annual was completed May 28, 2015.
- 2. Gas Wells: The gas wells are functioning correctly with regular pumping of condensate drains.
- 3. Header Lines: The header lines are functioning correctly.
- 4. Condensate Drains: All the condensate drains (CD) are working properly.
- 5. Knock Out Pot: The knock out pot remained dry the entire month.
- 6. Blower: The blower is functioning correctly.
- 7. Electric Controls: All electric controls are working properly.
- 8. Flare Assembly: The flare assembly is working correctly.

Cap Maintenance

Landfill cap in good condition.

Sanitary Leachate Collection System

The sanitary landfill dewatering system was operational all days during the month of August. The monthly summary for leachate levels are attached for your review.

A total of 24,000 gallons of sanitary leachate was shipped off site for disposal during the month of October. All 24,000 gallons were disposed at the Lower East Fork WWTP. All leachate wells are functioning. The leachate head levels remain below the approved alternate levels.

DK/dd

Cy: File (H.6)

LEACHATE HEAD LEVELS October 2015

m		October 20		1
WELL	DATE: 10/6/15	DATE: 10/15/15	DATE: 10/19/15	DATE: 10/27/15
1	1,9	1.8	1.8	1.7
2	1.2	1.2	12.1/1.2 A	12.6/1.2 A
3	Abandoned	Abandoned	Abandoned	Abandoned
4	1.6	1.8	1.9	1.8
5	1.7	1.7	1.9	1.9
6	1.5	1.5	1.6	1.6
. 7	1.6	1.5	2.1	2.1
8	1.5	1.5	1.0	1.0
9	1.9	1.6	1.5	1.5
10	1.7	1.7	1.6	2.0
11	1.5	1.5	2.2	2.2
12	1.1	1.1	1.1	1.1
13	1.5	1.6	10.9/1.7 B	1.6
14	1.7	1.7	1.6	1.6
15	1.6	1.6	2.0	1.8
16	1.7	1.7	2.0	2.2
17	1.7	1.7	1.5	1.5
18	1.9	1.8	1.8	1.9
19	1.6	1.7	1.5	1.5
20	1.6	1.7	1.4	1.3
21	1.6	1.6	1.4	1.5
22	1.8	1.8	1.4	1.4
23	1.5	1.5	1.5	1.5
24	1.4	1.4	1.4	1.4
1B	1.5	1.5	1.4	1.4
2B	1.7	1.7	1.7	1.7

A - Reset Coyote B - Install New Pump

MEMORANDUM

TO:

Dan Deborde

FROM:

Doug Kattwinkel

SUBJECT:

Sanitary Landfill System Report for the Month of November 2015

DATE:

December 8, 2015

Gas System Operation

The system was operational 1* day out of a possible 30 days. The system operated a total 2.5 hours for the month out of a possible 720 hours. The gas system operation averages for the month November are 14.5% methane and 675°F flare temperature. *Approximate runtime flare down frequently due to low gas production.

- 1. Explosive Gas Monitoring System: Gas monitoring for the semi-annual was completed November 30, 2015.
- 2. Gas Wells: The gas wells are functioning correctly with regular pumping of condensate drains.
- Header Lines: The header lines are functioning correctly.
- 4. Condensate Draine: All the condensate drains (CD) are working properly.
- 5. Knock Out Pot: The knock out pot remained dry the entire month.
- 6. Blower: The blower is functioning correctly.
- 7. Electric Controls: All electric controls are working properly.
- 8. Flare Assembly: The flare assembly is working correctly.

Cap Maintenance

Landfill cap in good condition.

Sanitary Leachate Collection System

The sanitary landfill dewatering system was operational all days during the month of November. The monthly summary for leachate levels are attached for your review.

A total of 36,000 gallons of sanitary leachate was shipped off site for disposal during the month of November. All 36,000 gallons were disposed at the Lower East Fork WWTP. All leachate wells are functioning. The leachate head levels remain below the approved alternate levels.

DK/dd

Cy: File (H.6)

LEACHATE HEAD LEVELS November 2015

		NOVEIIIDEI &	estantinguitusen - Servicen	
WELL	DATE: 11/3/15	DATE: 11/9/15	DATE: 11/17/15	DATE: 11/24/15
1	1.8	1.7	1.7	1.7
2	1.2	13.0/1.3 A	1.2	1.8
3	Abandoned	Abandoned	Abandoned	Abandoned
4	1.9	1.9	1.9	1.4
5	2.0	1.8	1.8	1.8
6	1.6	1.6	1.6	1.5
7	2.0	2.0	2.0	1.8
8	1.0	1.0	1.0	1.6
9	1,5	1.5	1.5	1.5
10	1.4	1.3	1.3	1.7
11	2.0	2.1	2.1	2.0
12	1,1	1.1	1.1	1.1
13	1.5	1.5	1.6	1.5
14	1.5	1.5	1.6	1.6
15	1.6	1.6	1.8	1.4
16	2.2	2.2	2.3	2.0
17	1.5	1.5	1.5	1.5
18	1.9	1.9	1.8	2.0
19	1.5	1.5	1.5	1.6
20	1.8	2.1	1.3	1.8
21	1.4	1,9	1.8	2.0
22	1.4	1.4	1.5	1.5
23	1.4	1.4	1.5	1.5
24	1.4	1.4	1.4	1.4
1B	1.4	1.5	1.3	1.8
2B	1.8	3.3/1.7 A	1.7	2.2

Client Sample Results

Client: Republic Services Inc

Project/Site: Aber Rd. Landfill - MP-290 analysis

Client Sample ID: MP-290B Lab Sample ID: 480-84096-1

Matrix: Water

TestAmerica Job ID: 480-84096-1

Date Collected: 07/14/15 12:00 Date Received: 07/17/15 09:30

Method: 8260C - Volatile On Analyte		unds by Go	C/MS RL	MDL	Unit	D	Prepared .	Analyzed	Dil Fac	Į
1,1,1-Trichloroethane	ND	-,	2.0	0.82				07/18/15 00:01	1	
1,1,2,2-Tetrachloroethane	ND		2.0	0.21	-			07/18/15 00:01	1	
1,1-Dichloroethane	ND		2.0	0.38	ug/L			07/18/15 00:01	1	
1,1-Dichloroethene	ND		2.0	0.29	_			07/18/15 00:01	1	
1,2-Dichloroethane	ND		2.0	0.21	ug/L			07/18/15 00:01	1	
2-Hexanone	ND		10	1.2	ug/L			07/18/15 00:01	1	
Acetone	ND		10		ug/L			07/18/15 00:01	1	
Benzene	ND		2.0	0.41	ug/L			07/18/15 00:01	1	
Bromoform	ND		2.0	0.26	ug/L			07/18/15 00:01	1	
Bromomethane	ND		2.0	0.69	ug/L			07/18/15 00:01	1	
Carbon disulfide	ND		2.0	0.19	ug/L			07/18/15 00:01	1	
Chlorobenzene	ND		2.0	0.75	ug/L			07/18/15 00:01	1	
Dibromochloromethane	ND		2.0	0.32	ug/L			07/18/15 00:01	1	
Chloroethane	15		2.0	0.32	ug/L.			07/18/15 00:01	1	
Chloromethane	ND		2.0	0.35	ug/L			07/18/15 00:01	1	
cis-1,2-Dichloroethene	3.0		2.0	0.81	ug/L			07/18/15 00:01	1	
cis-1,3-Dichloropropene	ND		2.0	0.36	ug/L			07/18/15 00:01	1	
Bromodichloromethane	ND		2.0	0.39	ug/L			07/18/15 00:01	1	
Dichlorodifluoromethane	DN		2.0		ug/L			07/18/15 00:01	1	
2-Butanone (MEK)	ND		10	1.3	ug/L			07/18/15 00:01	1	
4-Methyl-2-pentanone (MIBK)	ND		10	2.1	ug/L			07/18/15 00:01	1	
Methylene Chloride	ND		2.0	0.44	ug/L			07/18/15 00:01	1	
Styrene	ND		2.0	0.73	ug/L			07/18/15 00:01	1	
Tetrachloroethene	ND		2.0	0.36	ug/L			07/18/15 00:01	1	
trans-1,2-Dichloroethene	ND		2.0	0.90	ug/L			07/18/15 00:01	1	
trans-1,3-Dichloropropene	ND		2.0		ug/L			07/18/15 00:01	1	
Trichloroethene	ND		2.0	0.46	ug/L			07/18/15 00:01	1	
Trichlorofluoromethane	ND		2.0		ug/L			07/18/15 00:01	1	
Vinyl chloride	ND		2.0		ug/L			07/18/15 00:01	1	
Xylenes, Total	ND		2.0	0.66	ug/L			07/18/15 00:01	1	
Surrogate	%Recovery	Qualifier	Limits				Prepared	Analyzed	Dil Fac	
1,2-Dichloroethane-d4 (Surr)	106		86 - 118					07/18/15 00:01	1	
Toluene-d8 (Surr)	105		88 - 110					07/18/15 00:01	1	
4-Bromofluorobenzene (Surr)	110		86 - 115					07/18/15 00:01	1	
Method: Field Sampling - F										
Analyte	Result	Qualifier	NONE	NONE		D	Prepared	Analyzed	Dil Fac	
Field pH	6.78				SU			07/14/15 12:00	1	
Field Conductivity	1426				umhos/cm			07/14/15 12:00	1	
Field Temperature	16.1				Degrees C			07/14/15 12:00	1	
Field Turbidity	2.56				NTU			07/14/15 12:00	1	

Client Sample Results

Client: Republic Services Inc

Project/Site: Aber Rd. Landfill - MP-290B analysis

Client Sample ID: GW-101315AG-025 Lab Sample ID: 480-89202-1

Date Collected: 10/13/15 09:34 Date Received: 10/15/15 07:15

Method: 8260C - Volatile On Analyte	Result (RL	MDL	Unit	D	Prepared	Analyzed	Dil Fac
1,1,1-Trichloroethane	ND		2.0	0.82	ug/L		-	10/17/15 01:33	1
1,1,2,2-Tetrachloroethane	ND		2.0	0.21	ug/L			10/17/15 01:33	1
1,1-Dichloroethane	ND		2.0	0.38	ug/L			10/17/15 01:33	1
1,1-Dichloroethene	ND		2.0	0.29	ug/L			10/17/15 01:33	1
1,2-Dichloroethane	ND		2.0	0.21	ug/L			10/17/15 01:33	1
2-Hexanone	ND		10	1.2	ug/L			10/17/15 01:33	1
Acetone	ND		10	3.0	ug/L			10/17/15 01:33	1
Benzene	ND		2.0	0.41	ug/L,			10/17/15 01:33	1
Bromoform	ND		2.0	0.26	ug/L			10/17/15 01:33	1
Bromomethane	ND		2.0	0.69	ug/L			10/17/15 01:33	1
Carbon disulfide	ND		2.0	0.19	ug/L			10/17/15 01:33	1
Chlorobenzene	ND		2.0	0.75	ug/L			10/17/15 01:33	1
Dibromochloromethane	ND		2.0	0.32	ug/L			10/17/15 01:33	1
Chloroethane	13		2.0	0.32	ug/L			10/17/15 01:33	1
Chloromethane	ND		2.0	0.35	ug/L			10/17/15 01:33	1
cis-1,2-Dichloroethene	2.8		2.0	0.81	ug/L			10/17/15 01:33	1
cis-1,3-Dichloropropene	ND		2.0	0.36	ug/L			10/17/15 01:33	1
Bromodichloromethane	ND		2.0	0.39	ug/L			10/17/15 01:33	1
Dichlorodifluoromethane	, ND		2.0	0.68	ug/L			10/17/15 01:33	1
2-Butanone (MEK)	ND		10	1.3	ug/L			10/17/15 01:33	1
4-Methyl-2-pentanone (MIBK)	ND		10	2.1	ug/L			10/17/15 01:33	1
Methylene Chloride	ND		2.0	0.44	ug/L			10/17/15 01:33	1
Styrene	ND		2.0	0.73	ug/L			10/17/15 01:33	1
Tetrachloroethene	ND		2.0	0.36	ug/L			10/17/15 01:33	1
trans-1,2-Dichloroethene	ND		2.0	0.90	ug/L			10/17/15 01:33	1
trans-1,3-Dichloropropene	ND		2.0	0.37	ug/L			10/17/15 01:33	1
Trichloroethene	ND		2.0	0.46	ug/L			10/17/15 01:33	1
Trichlorofluoromethane	ND		2.0	0.88	ug/L			10/17/15 01:33	1
Vinyl chloride	ND		2.0	0.90	ug/L			10/17/15 01:33	1
Xylenes, Total	ND		2.0	0.66	ug/L			10/17/15 01:33	1
Surrogate	%Recovery	Qualifier	Limits				Prepared	Analyzed	Dil Fac
1,2-Dichloroethane-d4 (Surr)	110		86-118					10/17/15 01:33	1
Toluene-d8 (Surr)	107		88 - 110					10/17/15 01:33	1
4-Bromofluorobenzene (Surr)	103		86 - 115					10/17/15 01:33	1
Method: Field Sampling - F									
Analyte		Qualifier	NONE	NONE		D	Prepared	Analyzed	Dil Fac
Field pH	6.80				SU			10/13/15 09:34	1
Field Conductivity	1793				umhos/cm			10/13/15 09:34	1
Field Temperature	16.9				Degrees C			10/13/15 09:34	1
Field Turbidity	0.03				NTU			10/13/15 09:34	1

TestAmerica Job ID: 480-89202-1

Matrix: Water

EXHIBIT NO. 4

EXHIBIT NO. 4

LEVEL IV DATA VALIDATION SUMMARY REPORT

CMI MONITORING WELL SAMPLES APRIL 2015

CECOS ABER ROAD FACILITY, WILLIAMSBURG, OHIO

Level IV data validation has been completed for data generated by TestAmerica Laboratories, Inc. (TestAmerica), for selected Corrective Measure Implementation (CMI) monitoring well samples and associated field quality control samples collected from the CECOS International facility during April 2015. Data validation was performed as required by the CECOS International Quality Assurance Project Plan (QAPjP). In accordance with the CMI monitoring requirements and QAPjP, a minimum of 20 percent of all monitoring well samples collected in April 2015 received Level IV data validation. No CMI monitoring well samples were required to be collected in July 2015. A summary of the total set of samples validated is presented in Table 1. A glossary of the data validation qualifiers is presented as Table 2. A summary of the individual data validation summary reports attached to this report is included in Table 3.

Data validation was performed for these samples in accordance with the U.S. Environmental Protection Agency (USEPA) National Functional Guidelines, the respective analytical method, and/or the Data Validation Standard Operating Procedures as presented in the approved QAPjP. The latest version of the QAPjP (Revision 5) was submitted to USEPA in February 2006.

All CMI monitoring locations outside the slurry wall were sampled for the COI parameter list in April 2015. One CMI well located inside the slurry wall (MP-246) was also sampled in April. Level IV data validation was performed for these locations for those parameters stated in the facility's QAPjP. A total of fifteen monitoring wells were sampled and included in the CMI data package. Six associated field quality control samples were also collected during the April 2015 CMI monitoring event. TestAmerica Buffalo of Amherst, New York analyzed the samples using the analytical methods specified in the QAPjP.

The field quality control samples collected in April included:

- 2 Field blank samples
- 1 set of MS/MSD samples
- 1 Trip blank
- 2 Field duplicate samples

Field blanks, equipment blanks, field duplicates, and trip blanks were analyzed for the same parameters as their associated samples. The QAPjP also states that one set of MS/MSD samples be collected for every 20 samples. MS/MSD samples were submitted and analyzed by the lab and are indicated on the summary of samples received as being taken in well MP-238AR. All field Quality Control (QC) samples collected and analyzed met the Quality Assurance (QA) objectives specified in the QAPjP.

Limitations

Section 9, Data Reduction, Validation, and Reporting, within the QAPjP indicates that data reduction be conducted for field data and laboratory data; however, this report is limited to only the laboratory data. Additionally, the data quality assessment is limited to the review of off-site analytical laboratory data. This report addresses issues potentially impacting the usability of the laboratory data. If data validation findings were within acceptable criteria, limited discussion is presented. A discussion of data validation qualifiers (flags) applied to the data and reasons for the qualifiers are also presented. This report is organized by parameter groups.

Prepared by: SCS Engineers Project #05200007.02 July 31, 2015

TABLE 1
SUMMARY OF CMI MONITORING WELL SAMPLES TO BE VALIDATED

SAMPLE ID	APRIL 2015	JULY 2015 ¹
MP-207	COI/TCL	NS
MP-208	COI/TCL	NS
MP-238AR	COI/TCL	NS
MP-241AR	COI/TCL	NS
MP-249B	COI/TCL	NS
MP-275	COI/TCL	NS
MP-276	COI/TCL	NS
MP-299B	COI/TCL	NS
MP-303B	COI/TCL	NS
MP-304	CO1/TCL	NS
MP-304A	COI/TCL	NS
MP-305	COI/TCL	NS
MP-305A	COI/TCL	NS
MP-306A	COI/TCL	NS
U-11	NS	NS
U-12	NS	NS
MP-202	NS	NS
MP-219A	NS	NS
MP-222B	NS	NS
MP-224B	NS	NS
MP-246	VOC ²	NS
MP-248B	NS	NS

NS = Not Sampled for CMI

COI/TCL = Contaminants of Interest/Target Compound List in CMI O&M Manual APPENDIX IX = 40 CFR 264 Appendix IX List of Compounds

NOTES

- 1. The CMI Monitoring was revised in 2005 to only require semi-annual sampling. The sampling is performed in the months of April and October.
- 2. Well MP-246 was resampled in April 2015 for VOCs due to a Screening Level exceedance for 1,2-DCA in the October 2014 sampling results.

TABLE 2

GLOSSARY OF DATA VALIDATION QUALIFIERS

- U The analyte was analyzed for but not detected. The associated numerical value is at or below the MDL.
- R The reported result has been qualified as unusable due to gross violations of one or more quality control criteria. This flag does not address the presence or absence of the analyte of concern rather it addresses one or more major QC problems associated with the reported result. If the analyte qualified is critical to the project, resampling and reanalysis of the qualified result may be required.
- UJ The analyte was considered estimated non-detect. The associated numerical detection limit has been qualified as estimated due to a QA/QC anomaly and should be considered estimated.
- 10U The analyte was determined to be non-detect due to its presence in the field and/or laboratory blank associated with the sample. The reported result has been qualified as not detected due to the blank contamination. The numerical value listed in front of U is the lab's Project Reporting Limit (PRL) for the analyte and will change according to the reported PRL for that analyte.
- D The result was determined in a diluted sample.
- J The analyte was analyzed for and was positively identified but the associated numerical value may be imprecise due to a quality control anomaly. The data is considered usable for many purposes. The 'J' flag is also used to indicate results above the method detection limit (MDL) but below the reporting limit. These results should be considered estimated.
- B The analyte was analyzed for and positively identified. The reported result should be considered estimated due to negative contamination in the associated laboratory blank.
- E Identifies compounds whose concentrations exceed the calibration range of the instruments for specific analysis.
- NJ The analysis indicates that the analyte is "tentatively identified" and the associated numerical is estimated. The quantification is a result of multiple QA/QC failures not sufficient enough to reject the result.

TABLE 3
SUMMARY OF DATA VALIDATION REPORT ATTACHMENTS

ATTACHMENT	DATA VALIDATION REPORT
4-1	APRIL 2015 COI VOC

ATTACHMENT 4-1

LEVEL IV DATA VALIDATION SUMMARY REPORT

CECOS INTERNATIONAL VOC ANALYSIS

APRIL 2015 SAMPLING EVENT

I. INTRODUCTION

This data package included a total of fifteen monitoring well samples, four associated field quality control samples, one set matrix spike/matrix spike duplicates (MS/MSD), and one trip blank. TestAmerica of Amherst, NY analyzed the samples using the 8260B analytical method specified in the QAPjP for the CECOS Target Analyte and Compounds of Interest list in Table 1-1A of the QAPjP.

VALIDATION SUMMARY

II. Data Deliverables

The data package contained all deliverables and was generally acceptable for use.

III. Technical Holding Times

All samples were analyzed within the acceptable holding time of 14 days for preserved and cooled samples.

IV. Instrument Performance Check

An instrument performance check was performed at the beginning of each analytical sequence using bromofluorobenzene (BFB). No transcription or calculation errors were noted. All performance checks met the criteria stated in the QAPjP.

V. Initial Calibration (ICAL)

ICALs were performed at an appropriate frequency and were performed within 12 hours of the instrument performance check. The following variances from the QAPjP were noted for the ICALs in the data package:

- The number and concentrations of the calibration standards differed from those stated in the QAPiP. However, the CRQL was bracketed for all target analytes.
- Table 1 of the QAPjP lists pentafluorobenzene as one of the internal standards for target compounds; however, the lab utilized 1,4-dichlorobenzene-D4 as an internal standard instead of pentafluorobenzene. Table 1 of the QAPjP lists 1,4-difluorobenzene as one of the internal standards for target compounds; however,

the lab utilized fluorobenzene as an internal standard instead of 1,4-difluorobenzene.

- When calculating Relative Response Factors (RRFs), some target compounds were assigned to different internal standards than those assigned in Table 1 in the QAPjP.
- The laboratory considers the maximum percent Relative Standard Deviation (RSD) for some compounds to be 20% rather than the 30% limit included in the QAPjP.

The initial calibration results for the following parameters did not meet the minimum RRF criteria of 0.3.

HP5975D	1,4-Dioxane	RRF = 0.0073
HP5973N	Isobutyl alcohol	RRF = 0.0170
	1,4-Dioxane	RRF = 0.0034

These parameters are not COIs, therefor no results have been qualified.

VI. Continuing Calibration (CCAL)

All of the compounds in the five CCALs met the Percent Difference (% D) criteria stated in the QAPjP, with the following exceptions.

•	HP5973N	Acrolein	%D = -38.8
•	HP5973N	1,4-Dioxane	%D = 28.1

Because the above are not compounds of interest, no results have been qualified.

VII. Blanks

Sufficient laboratory, field, and equipment blanks were included in the data packages to meet the requirements of the QAPjP. All samples were run within 12 hours of a method blank. No compounds of interest were reported in the method blanks. No compounds of interest were reported in the other types of blanks.

VIII. System Monitoring Compounds

TestAmerica utilized 1, 2-dichloroethane-d4 and 4-bromofluorobenze as two of the three surrogates compared to dibromofluoromethane and bromofluorobenzene as listed in the QAPjP. Percent recoveries for the surrogates fell within the ranges presented in the QAPjP.

IX. Matrix Spike/Matrix Spike Duplicates (MS/MSD) and Laboratory Control Samples (LCS)

The data package contained four LCS samples and one MS/MSD sample pair. The QAPjP includes the evaluation of Percent Recovery (%R) and Relative Percent Difference (RPD) for five compounds for the MS/MSD and LCS samples. The lab evaluated four of the five

compounds in the Form III summary for each sample. All %R and RPD values were within the laboratory specific limits required by the QAPjP.

X. Internal Standards (IS)

All IS area counts and retention times were within the limits stated in the QAPjP. No transcription errors were noted.

XI. Target Compound Identification

All IS area counts and retention times were within the limits stated in the QAPjP. No transcription errors were noted.

XII. Compound Quantitation and Reported CRQLs

All compounds detected appeared to meet the criteria stated in the QAPjP.

XIII. Tentatively Identified Compounds

Tentatively identified compounds were not required to be evaluated for this sampling event.

XIV. Field Duplicates

The data package included two duplicates; DUPLICATE-CMI #1 and DUPLICATE-CMI #2. No reportable concentrations of target compounds were detected in either the original samples or the duplicates.

XV. Overall Assessment of Data

The percent completeness of data equals 100 % (no analytical data was rejected). No deficiencies that warranted qualification were found. No qualified samples are presented on Table 4-1. None of data results were rejected due to quality control deficiencies.

A summary of the validated VOC detections for this CMI monitoring event is presented as Table 4-2. Only well MP-246, located inside the CMI slurry wall, had validated detections of VOC compounds above the lab reporting limit.

TABLE 4-1 QUALIFIED SAMPLES APRIL 2015

Sample Name	Lab Sample ID	Qualification
MP-275	480-78109-1	None
MP-241AR	480-78109-2	None
MP-238AR	480-78109-3	None
MP-305	480-78109-4	None
MP-305A	480-78109-5	None
MO-304A	480-78109-6	None
MP-276	480-78109-7	None
MP-304	480-78109-8	None
MP-249B	480-78109-9	None
DUPLICATE-CMI #2	480-78109-10	None
MP-207	480-78109-11	None
MP-208	480-78109-12	None
FIELD BLANK-CMI #2	480-78109-13	None
MP-299B	480-78109-14	None
MP-306A	480-78109-15	None
DUPLICATE-CMI #1	480-78109-16	None
FIELD BLANK-CMI #1	480-78109-17	None
MP-303B	480-78109-18	None
TRIP BLANK	480-78109-19	None
MP-246	480-78111-1	None

TABLE 4-2 **SUMMARY OF VOC DETECTIONS APRIL 2015**

CECOS Sample ID	Lab Sample ID	Analyte	Result (ug/L)	Lab Flag	SCS Flag
MP-246	480-78111-1	1,1,1-Trichloroethane	60		
		1,1-Dichloroethane	45		
		1,1-Dichloroethene 1	16		
		1,2-Dichloroethane ²	6.2		
		Benzene	1.1	J	J
		Chloroethane	0.65	J	J
		cis-1,2-Dichloroethene	3.5		·
		Tetrachloroethene ²	65		
		Trichloroethene 2	7.3		
		Trichlorofluoromethane	5.0		
		Vinyl Chloride	1,0	J	j

NOTES:

Bold - Result exceeds CMI Cleanup Standard concentration.

1. COI Compound, Cleanup Standard = 7 ug/L

2. COI Compound Cleanup Standard = 5 ug/L

EXHIBIT NO. 5

EAGON & ASSOCIATES, INC.

Consulting Geologists

100 Old Wilson Bridge Road, Suite 115 / Worthington, Ohio 43085 / (614) 888-5760 / FAX (614) 888-5763

December 3, 2015

Mr. Daniel Deborde CECOS International, Inc. 5092 Aber Road Williamsburg, Ohio 45176

RE: Administrative Order on Consent, O&M Progress Report No. 39

Exhibit 5 - Corrective Measures Implementation Performance Monitoring Evaluation

CECOS International, Inc. - Aber Road Facility

Docket No. V-W-024-94

EPA I.D. No. OHD 087 433 744

Dear Mr. Deborde:

Transmitted herewith is the Corrective Measures Implementation (CMI) Performance Monitoring Evaluation for CMI data collected during the October 2015 monitoring event at the closed Aber Road Facility. This evaluation is being provided to you for inclusion as Exhibit 5 of the Operation and Maintenance (O&M) Progress Report No. 39 that must be submitted to the United States Environmental Protection Agency (U.S. EPA) by December 10, 2015.

OCTOBER 2015 MONITORING RESULTS

Compounds of Interest/Target Compound List Volatile Organic Compound Results – Outside Slurry Wall Monitoring Wells

The October 2015 monitoring event was conducted in accordance with Section 5 of the July 2009 CMI O&M Manual. The event represented year seven, quarter four of CMI monitoring as listed on Table 5.2 (Post Shutdown Monitoring Program/Groundwater Monitoring) of the CMI O&M Manual. Monitoring wells located both inside and outside the slurry wall were sampled for Compounds of Interest/Target Compound List (COI/TCL) volatile organic compounds (VOCs). Monitoring locations located outside the slurry wall are sampled semiannually (spring and fall). Locations inside the slurry wall are sampled annually (fall).

During the October 2015 event, no COI VOCs were detected at or above their respective method detection limits (MDLs) in the monitoring locations outside the slurry wall. A summary of the 2015 COI VOC results is presented on attached Table1. Groundwater Cleanup Standards (GWCS) shown on Table 1 and listed in Section 5.2 of the July 2009 CMI O&M Manual continue to be achieved for the COIs at the 14 CMI wells located outside the slurry wall.

As shown on Table 1, COI VOCs were detected at or above their respective practical quantitation limits (PQLs) in four monitoring wells (MP-202, MP-222B, MP-224B, and MP-246) and one underdrain (U-12) located inside the slurry wall. Those results were within the range of historical values observed at each location, with some results continuing to decline to concentrations near or below historical minimums (e.g., 1,2-Dichloroethane at MP-202 and MP-224B; and 1,1-Dichloroethylene at MP-246). In addition, no TCL VOCs for which a GWCS has not been established were detected at or above their respective MDLs inside or outside the slurry wall during the October 2015 event.

Semiannual Gradient Analysis and Elevation Differences for Nested Wells/Piezometers

Section 5.6 of the July 2009 CMI O&M Manual requires semiannual groundwater elevation measurements to be collected for a minimum of five years at six well clusters inside and outside the slurry wall to assist in identifying hydraulic gradients across the slurry wall following shutdown of the gradient control pumping system in 2009. The initial five-year gradient monitoring period was completed as of the October 2013 event. As a result, in the future CECOS may request U.S. EPA approval to reduce the measurement of groundwater elevations to an annual basis for gradient analysis.

Groundwater elevation measurements were collected for the CMI gradient analysis well network on October 12, 2015, prior to initiating the CMI groundwater sampling event. Figure 1 shows the locations of the six nested piezometers/wells. As required in Section 5.7.2 of the CMI O&M Manual, gradient evaluations for the six nested piezometers/wells are presented in Exhibit 2 and time-series plots depicting elevation differences for each nested piezometer are presented herein as Figures 2 through 7.

During the October 2015 event, well pairs #3 (880PZ-2 and MP-305A) and #4 (MP-238AR and 880PZ-3) indicated inward gradients. Well pairs #1 (USPZ-1 and MP-303B), #2 (880PZ-1 and MP-208), #5 (880PZ-4 and MP-304A), and #6 (880PZ-5 and MP-241AR) indicated outward gradients. Outward gradients have been observed at these well pairs during past events and conditions observed in October 2015 were generally within the range of historic observations (See Figures 2 through 7). Well pairs #1 (Figure 2) and #4 (Figure 5) display seasonal effects on gradient relationships, with inward gradients commonly occurring.

As discussed in the June 30, 2008 "Aber Road Petition to Cease Groundwater Recovery", advective groundwater flow through the slurry wall is negligible due to the low hydraulic conductivity of the bentonite and the fact that the Upper Sand and 880 Sand zones were removed during slurry wall construction; therefore, the presence of an outward gradient is not expected to result in contaminant transport across the slurry wall. Semiannual monitoring of wells outside the slurry wall continues to demonstrate that COI/TCL VOCs are not being transported across the slurry wall's hydraulic barrier.

Semiannual Potentiometric Surface Maps

Section 5.6 of the July 2009 CMI O&M Manual requires monitoring wells listed in Section 5.4 of the Manual to be used in developing semiannual groundwater elevation maps both inside and outside the slurry wall. This is as specified in Condition #1 of the March 31, 2009 U.S.

EPA "Final Approval with Conditions/Modifications to Shutdown the Groundwater Gradient Control System."

Potentiometric surface maps for CMI wells screened in the Upper Sand, 880 Sand, and Bedrock Till Interface (BTI) Zones in October 2015 are shown on Figures 8, 9 and 10, respectively. Groundwater flow conditions in the Upper Sand and 880 Sand Zones are similar in nature to historical conditions. The removal of formation material during cell construction and installation of the slurry wall as a hydraulic barrier resulted in localized isolation of the remaining sands. Therefore, water levels in the Upper Sand and 880 Sand in the CMI area generally do not define well organized potentiometric surfaces. Groundwater flow in the BTI, which is below the depth of the slurry wall, was toward the southwest in the vicinity of the CMI area during the event, consistent with previous observations.

COMPARISON OF SIX COI/TCL VOC RESULTS AT MP-219A, MP-246, & MP-248B TO CBPSs & SCREENING LEVELS

The June 30, 2008 Aber Road Petition to Cease Groundwater Recovery submittal noted six COI/TCL VOCs at wells inside the slurry wall with concentrations above the Consent Order-specified GWCSs intended to be applied at the point of compliance wells located outside the slurry wall. These compounds are 1,2-dichloroethane, 1,1-dichloroethylene, tetrachloroethylene, 1,1,1-trichloroethane, trichloroethylene, and vinyl chloride. The June 30, 2008 submittal contained concentration-based performance standards (CBPS) for these six parameters calculated such that if concentrations of these parameters at wells inside the slurry wall were below the CBPSs, then concentrations of these parameters in wells outside the slurry wall would remain below GWCSs for 30 years after System shutdown. The May 30, 2008 Aber Road Petition to Cease Groundwater Recovery (including an August 14, 2008 supplement) also developed Screening Levels (below the CBPSs) for the six COI/TCL VOCs for wells MP-219A, MP-246, and MP-248B, which are located inside the slurry wall boundary. The Screening Levels were calculated using conservative fate-and-transport assumptions such that if concentrations of these parameters at wells inside the slurry wall were below the Screening Levels, then concentrations of these parameters in wells outside the slurry wall would be expected to remain below detection for 30 years after system shutdown. The CBPSs and Screening Levels for 1,2-dichloroethane, 1,1-dichloroethylene, tetrachloroethylene, 1,1,1-trichloroethane, trichloroethylene, and vinyl chloride can be found in Section 5.8 of the July 2009 CMI O&M Manual.

Attached Table 2 contains a comparison of the October 2015 annual results from monitoring wells MP-219A, MP-246, and MP-248B, located inside the slurry wall, to the CBPSs and Screening Levels calculated for 1,2-dichloroethane, 1,1-dichloroethylene, tetrachloroethylene, 1,1,1-trichloroethane, trichloroethylene, and vinyl chloride, where detected. It is noted that there were no COI/TCL VOC detections at or above respective method detection limits at MP-219A or MP-248B for the event.

None of the October 2015 COI/TCL VOC results for any of the three wells approached or exceeded their respective CBPSs or Screening Levels for the six VOCs, with the exception of the Screening Level for 1,2-Dichloroethane at Upper Sand well MP-246. The 1,2-Dichloroethane concentration of 21 ug/L at MP-246 in October was above the Screening Level of 15 ug/L. As

required by Section 5.10 of the July 2009 CMI O&M Manual, an evaluation of the Screening Level exceedance and recommendations for additional action are presented below.

Evaluation of the Screening-Level Exceedance at MP-246

Section 5.10 of the O&M Manual requires that an evaluation of a Screening Level exceedance be completed and submitted to U.S. EPA for approval "within 30 days of receipt of validated data." The CMI data validation is not required to be completed until the reporting period following each semiannual sampling event. Therefore, the validation for the October 2015 event will be completed by spring 2016 and presented in Progress Report No. 40 due June 10, 2016. However, we have completed our evaluation of the Screening Level exceedance for 1,2-dichloroethane (1,2-DCA) at MP-246 and have developed recommendations for additional actions moving forward.

The October 2015 1,2-DCA concentration of 21 ug/L at MP-246 remains below the CBPS of 37 ug/L. The result is above 2012 (12 ug/L) and 2013 (1.6J ug/L) values; however it is below the 2014 result of 22 ug/L and is significantly below the maximum historic concentration of 1,880 ug/L. The October 2015 result is within the range of concentrations observed since 2000 (≤ 58 ug/L), where the overall trend is downward (Figure 11) with more widely variable seasonal fluctuations observed since 2011. Figure 11 displays water-level elevations in the well since 2011 that show periods of seasonally lower water levels have corresponded to somewhat increased concentrations in the well. In addition, review of water-level fluctuations in the context of routine gradient analysis shows that, since pumping was discontinued inside the slurry wall, hydraulic gradients across the slurry wall have been more frequently inward than outward at Well Pair #1 located nearest to MP-246 (Figures 2 and 8). This suggests that, on average, the potential for groundwater transport is from outside the slurry wall to inside in the vicinity of MP-246.

A time-series graph of all constituents detected during the October 2015 event is presented on Figure 12 and includes results collected since 2000. Figure 12 shows that concentration trends remain predominantly downward for the constituents commonly detected at well MP-246. Figure 12 shows that October 2015 concentrations of 1,1,1-Trichloroethane and 1,1-Dichloroethylene were at their lowest levels observed to-date and several other constituents were near their lowest observed concentrations. This suggests that the Screening Level exceedance for 1,2-DCA at MW-246 occurred as overall groundwater quality conditions continue to improve at the well, including since system shutdown in 2009.

The October 2015 results at nearby Upper Sand wells located outside the slurry wall, including MP-207, MP-299B, and MP-303B (Figure 8), remain nondetect for 1,2-DCA (Table 1) and demonstrate that the slurry wall continues to provide an effective barrier to contaminant migration in the MP-246 area. The outside results together with the average inward gradient in the area indicate that the exceedance of the very conservative Screening Level for 1,2-DCA at MP-246 is not reflective of an imminent potential for the Action Level of 3 ug/L or the GWCS of 5 ug/L to be exceeded beyond the slurry wall.

Another significant variable considered during the evaluation of the Screening Level exceedance was the nature of the Upper Sand in the vicinity of MP-246 and the completion and performance characteristics of MP-246, in general. The Upper Sand horizon is approximately 1.5 feet

thick at the well, from 19.5 to 21 feet below ground, and the areal extent of the zone is entirely truncated by the slurry wall. During slurry wall construction, the formation was removed via trenching and was replaced with a soil-bentonite slurry barrier. The slurry wall trench was excavated to a minimum width of two-feet. The trench extended vertically, through the Upper Sand, to below the 880 Sand. In addition to this substantial hydraulic barrier to horizontal transport, MP-246 is a low-yielding well that typically purges to dryness using volumetric purging sampling methods, which demonstrates low hydraulic conductivity of the Upper Sand zone in the vicinity of the well.

The combination of the formation characteristics in the MP-246 area, the tendency for inward groundwater flow potential across the slurry wall, and the limited areal extent of the zone due to its removal during slurry wall construction minimize the likelihood that a low-level exceedance above the Screening Level will result in detections of 1,2-DCA outside the slurry wall.

In addition to the above analysis, review of the information presented in the 2008 *Petition to Cease Groundwater Recovery* indicates that a calculated value of 18 (ml/g) was used for the organic carbon partition coefficient (K_{OC}) for 1,2-DCA. Published references for actual experimental values, including supporting documentation provided in USEPA's National Primary Drinking Water Regulations, indicate K_{OC} values of at least 33 for silt loam soils such as the Upper Sand zone and the soil matrix used in the slurry. Following the approach described in the petition, using a K_{OC} value of 33 for 1,2-DCA would result in a Screening Level of 22 ug/L (verses 15 ug/L). The resulting CBPS would be 54 ug/L (verses 37 ug/L) to prevent the Cleanup Standard of 5 ug/L from potentially being exceeded in 30 years. Therefore, applying the experimentally-derived K_{OC} value of 33, the October 2015 1,2-DCA result of 21 ug/L at MP-246 does not exceed the resulting Screening Level of 22 ug/L. More importantly, the October result would still be substantially below the alternate CBPS of 54 ug/L.

As noted above and discussed in the 2008 petition to discontinue pumping operations, the calculated Screening Levels were developed as conservative (i.e., low-end) values for triggering additional evaluation of future results. Combined with the above discussion, it is our conclusion that no imminent potential exists for contaminant migration beyond the slurry wall based on the October 2015 sampling results.

Recommended Actions Based on the Evaluation of the Screening-Level Exceedance at MP-246

Section 5.10 of the O&M Plan states: "Response actions [following a screening level exceedance] may include an upgraded monitoring program to assess and predict the possible impacts on groundwater outside the slurry wall, and/or resuming the pumping of the groundwater gradient control trench (at MP-246) and/or certain wells (at MP-219A and MP-248B)." Based on the evaluation of the single Screening Level exceedance discussed above, resumption of active gradient control operations is not warranted at this time; however, augmenting the CMI ground-water monitoring program to allow for supplemental data collection to better characterize the nature of the October 2015 1,2-DCA concentration at MP-246 is warranted. To accomplish this, CECOS proposes to perform supplemental sampling of monitoring well MP-246 during 2016. The well is normally sampled annually, during the fourth quarter of each year. During 2016, the well will be added to the semiannual (spring) CMI ground-water monitoring event and sampled for the full list of COI/TCL list of compounds. Wells outside the slurry wall will continue to be sampled semiannually including during the spring 2015 event. The results of the spring event at MP-246 will be compared to

Screening Levels and previous results and recommendations for any additional actions that may be appropriate will be provided in Progress Report No. 40 due June 10, 2016.

Please contact me at (614) 888-5760 if you have any questions.

Sincerely,

Michael T. Gibson, CPG

Hydrogeologist

MTG/ns encl.

FIGURES






FIGURE 1. NESTED MONITORING WELL / PIEZOMETER LOCATIONS




Aber Road Facility Williamsburg, Ohio

Figure 2
Elevation Differential for
Well Pair 1: MP-303B & USPZ-1




Aber Road Facility, Williamsburg, Ohio

FIGURE 1. NESTED MONITORING WELL / PIEZOMETER LOCATIONS




Aber Road Facility Williamsburg, Ohio

Figure 2
Elevation Differential for
Well Pair 1: MP-303B & USPZ-1




Williamsburg, Ohio

Figure 3
Elevation Differential for
Well Pair 2: MP-208 & 880PZ-1



Aber Road Facility Williamsburg, Ohio

Figure 4
Elevation Differential for
Well Pair 3: MP-305A & 880PZ-2




Aber Road Facility Williamsburg, Ohio

Figure 5
Elevation Differential for
Well Pair 4: MP-238AR & 880PZ-3

Aber Road Facility Williamsburg, Ohio

Figure 6
Elevation Differential for
Well Pair 5: MP-304A & 880PZ-4

Note: Positive differential represents inward gradient across the slurry wall.



8

6

4

2

Elevation Differential

Aber Road Facility Williamsburg, Ohio

Figure 7
Elevation Differential for
Well Pair 6: MP-241AR & 880PZ-5

Aber Road Facility, Williamsburg, Ohio

FIGURE 8. POTENTIOMETRIC SURFACE OF THE UPPER SAND ZONE - CMI WELLS, OCTOBER 12, 2015

Aber Road Facility, Williamsburg, Ohio

Contour (ft MSL)

WATER LEVELS COLLECTED BY EAGON & ASSOCIATES, INC. ON OCTOBER 12, 2015

FIGURE 9. POTENTIOMETRIC SURFACE OF THE 880 SAND ZONE - CMI WELLS, OCTOBER 12, 2015

600


300 GRAPHIC SCALE IN FEET


Aber Road Facility, Williamsburg, Ohio

WATER LEVELS COLLECTED BY EAGON & ASSOCIATES, INC. ON OCTOBER 12, 2015

600

GRAPHIC SCALE IN FEET





TABLES

TABLE 1. SUMMARY OF OCTOBER 2015 CONSTITUENT OF INTEREST (COI) RESULTS AND COMPARISON TO CLEANUP STANDARDS AND ACTION LEVELS' CECOS INTERNATIONAL, INC. - ABER ROAD FACILITY

Well	Sampling Date	Acetone (ug/L)	Benzene (ug/L)	Methyl ethyl ketone (ug/L)	Chloro- ethane (ug/L)	Dichloro- difluoro- methane (ug/L)	1,1-Dichloro- ethane (ug/L)	1,2-Dichloro- ethane (ug/L)	1,1- Dichloro- ethylene (ug/L)	cis-1,2- Dichloro- ethylene (ug/L)	trans-1,2- Dichloro- ethylene (ug/L)	Methylene chloride (ug/L)	Tetra- chloro- ethylene (ug/L)	1,1,1- Trichloro- ethane (ug/L)	Trichloro- ethylene (ug/L)	Trichloro- fluoro- methane (ug/L)	Vinyl chloride (ug/L)
Cleanup Stand	lard (ug/L) ¹	10000	5	61000	292000	20000	10000	5	7	70	100	5	5	200	5	31000	2
Basis		Health	MCL	Health	Health	Health	Health	MCL	MCL	MCL	MCL	MCL	MCL	MCL	MCL	Health	MCL
Action Level (ug/L) ¹		4000	3	1900	43000	1000	2000	3	4	40	50	3	3	100	3	3000	1
30493603W33C03co		again and Adag	enegative(vegfere	spijija prompi	eggapanjevensj	Maria de propositi	Wells Lo	cated Outside	the Slurry V	Vall	guran kiran bagi	A branchen				Marianaeriyesi	
MP-207	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-208	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-238AR	10/13/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-241AR	10/13/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-249B	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-275	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-276	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-299B	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-303B	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-304	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-304A	10/12/2015	<10	<2	<10	<2	<2.	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-305	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-305A	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
MP-306A	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2
400000000000000000000000000000000000000	Waldenschieberger	riversitieses		420860460agsi			Vells/Underdr							2 2 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0.51.00	-2	<2
MP-202	10/13/2015	<10	0.64 (Л)	<10	<2	<2	5.5	1.9 (J)	<2	1.0 (J)	<2	<2	<2	<2	0.51 (J)	<2	
MP-219A	10/13/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2 <2
MP-222B	10/13/2015	<10	2.4	<10	0.55 (J)	3.2	1.4 (J)	62	<2	1.7 (J)	<2	0.50 (J)	<2	<2	<2	<2	<2
MP-224B	10/13/2015	<10	<2	<10	<2	<2	4.2	<2	<2	<2	<2	<2	<2	<2	<2	<2 <8	<8
MP-246	10/13/2015	<40	<8	<40	<8	<8	75	21	12	12	<8	<8	110	20	13	- 1	<2
MP-248B	10/12/2015	<10	<2	<10	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	<2	
U-11	10/13/2015	<10	<2	<10	<2	<2	0.99 (J)	<2	<2	0.98 (J)	<2	<2	<2	<2	<2	₹2	<2 2.5
U-12	10/13/2015	<10	<2	2.4 (J)	<2	<2	1.4 (J)	<2	<2	8.5	<2	<2	<2	<2	<2	~	4.5

¹ Cleanup Standards and Action Levels are relevant to Corrective Measures Implementation (CMI) wells located outside the slurry wall. J: Estimated results between the method detection limit (MDL) and reporting limit.

TABLE 2.
CMI COI COMPOUND DETECTIONS AT MP-246, MP-219A, AND MP-248B
OCTOBER 2015 MONITORING EVENT
CECOS INTERNATIONAL, INC. ABER ROAD FACILITY

Well	Constituent of Interest (COI)	Result (ug/L)	Concentration-Based Performance Standards (CBPS) (ug/L)	Screening Level (ug/L)
MP-219A	No detections	NA	NA	NA
	1,1,1-Trichloroethane	20	. 130,000	1,350
	1,1-Dichloroethylene	12	213	62
MP-246	1,2-Dichloroethane	21	37	15
	Tetrachloroethylene	110	60,000,000	30,000,000
	Trichloroethylene	13	1,200	500
MP-248B	No detections	NA	NA	NA

Notes:

Per the July 13, 2009 CMI Operations and Maintenance Manual, results for wells MP-246, MP-219A, and MP-248B are to be compared to calculated CBPS and Screening Levels for six COI compounds (1,2-dichloroethane, 1,1-dichloroethylene, tetrachloroethylene, 1,1,1-trichloroethane, trichloroethylene, and vinyl chloride). Results not listed are non-detect (<MDL).

MP-219A and MP-248B had no detections of COIs above the MDL during the October 2015 event.



1800 Indian Wood Circle, Maumee, Ohio 43537 Tel: 419.891.2222 Fax: 419.891.1595 www.MannikSmithGroup.com



MEMO

To:

Dan Deborde, Environmental Manager, Republic Services, Inc.

From:

Matthew Barnett

CC:

Joe Montello, Hydrogeology Manager, Republic Services, Inc.; Mike Gibson, Eagon & Associates, Inc.

Date:

October 21, 2015

Project #:

R1050012

Re.

October 2015 CMI Groundwater Sampling Audit at the CECOS Aber Road Facility

This memo documents the completion of the Groundwater Sampling Audit conducted during the October 2015 groundwater monitoring event for the Corrective Measures Implementation (CMI) program at the Closed CECOS facility at 5092 Aber Road in Williamsburg, Ohio. Detailed notes regarding the findings of the audit are provided on the attached field audit checklist from the CMI QAPP.

The audit was completed by Matthew Barnett of The Mannik & Smith Group on October 12-13, 2015 during purging and sampling of the CMI wells. Eagon & Associates, Inc. (Eagon) conducted the sampling event. Eagon personnel performing the CMI sampling included:

CMI Sampling Team

Chris Gordon

Nick Karow

Andy Graham (field team leader)

Andy Graham was the field team leader for this sampling event and coordinated the CMI sampling event well. Additional Eagon staff on site included Nelson Novak who conducted the DMP sampling and Ryan Hansel to sample the underdrains (neither part of the CMI audit).

During the audit, the following activities were observed: field preparation activities, meter calibration, water level measurements, well purging, well sampling, QA/QC sample collection, groundwater sample packing/handling, record keeping activities, and purge water handling.

Well purging and sampling were observed at multiple locations including wells MP-202, MP-207, MP-208, MP-219A, MP-222B, MP-224B, MP-238AR, MP-241AR, MP-249B, MP-276, MP-303B, MP-304A, MP-305, and MP-305A.

Based on my observations, the CMI sampling team completed the work in compliance with the QAPP and SAP. The Eagon sampling team was well organized, knowledgeable, and had an efficient preparation, decontamination, sampling, and sample-handling system in place. There were no significant issues identified in the field that would affect data quality.

Please call me at 614.214.6879 should you have any questions.

GROUND WATER SAMPLING FIELD AUDIT CHECKLIST October 12 3 13, 2015

		BFI Site: Cocos Alber Ropo Facility
	1. 2.	Audit Dates: 0212-13, 2215
	3.	Sampling Crew Company Name and Address: Emplo 3 Accordes
	4.	Sampling Crew names and number of times at site: 1400 (120 homes)
	5.	Who is responsible for Health and Safety: And Graham
	6.	Has Crew reviewed the site Health and Safety Plan: Ves
	7.	Is there a Site Specific Sampling Plan:
		 a. If yes, has sampling crew reviewed Sampling Plan: Yes b. If no, what is the SOP that is followed for sampling this site:
	8.	Has crew read BFI Corporate Sampling SOP:
	9.	Has crew read the EPA's 1986 or 1992 TEGD:
	10.	Has crew read the EPA's Subtitle "D" Final Rule:
	11.	Who packs sampling crew's equipment and bottles:
	12.	Who decontaminates field equipment between sites:
	13.	Were instruments calibrated before coming to site:
	14.	Have crew members read own SOP or manufacturer's instructions for instrument operations:
	15.	Have arrangements been made with all labs that samples are to be delivered to: Yes TA council picks up samples as needed
	16.	Has crew signed in daily:
	17.	Have arrangements been made with BFI site contact: Yes - Dan Deboade
	18.	Where are all keys stored: All locks bened alive - Coson has set / set in key box in lab.
	19.	Vehicle used: O Topic Files prekue laucies
Coma	tents:	
В.	INIT	IAL MONITORING
	I.	Is air monitored immediately upon the opening of the well inner cap: $\frac{N/\Delta}{\Delta}$
	2.	Are procedures needed for immiscible layer detection:

AUDIT/93

Mathew Barnett
The Mannile & Smith Grove
1800 Italian Wood Checke
Mannee, OH 43537
(419) 891-2222

	3.		er level measured to the nearest .01 foot:	
	4.	Is a place made be measured	arked on the well indicating the point where the water level is to from every time: Yes marks an act such cap	
	5.		I winter laurely was round within burning form (74) barrage	
	6.		well double manufact to the manufact of the little of the	
	7.		level indicator line and probe wiped with a DI water moistened	
			e probe is being realed up/what are water level indicator line	į.
		decontamina	tion procedures: Yes You'nox sear to loved by	
			Si Care	
	8.	Is the probe	decontaminated between wells: Vec	
		2.	How: MANN SORAN -77 DI CINSC	
	9.	Is the well co	ondition recorded on a well condition log:	
			;	
Comi	nents: .			
****************	·			
			,	
٠. 	PUR	<u>GING</u>		
	•	Granter	purge devices are used: <u>dedicated bladder pumps</u>	
			purge devices are used:	
		2.	If Bailer:	
			Is bailer stored in the well:	
			- married annual in name work store from the other of a	
			PVC or stainless steel hook: How often is line replaced:	
			What is bailer line made of:	
			How is bailing line, hook, and lowering mechanism How is bailing line, hook, and lowering mechanism	
			decontaminated between wells:	
			ACTAINMENT DELACTI METT.	
			Is care taken when raising and lowering bailer to ensure	
			water and well integrity:	
			What is bailer made of:	
			Does bailer touch the ground or any other contaminating	
			source: NA	
		b.	If Pump: dedicaled be blader parces	
			What is power source: Contraised and Contrained	
			If a generator is used, where is generator located while	
			well is being purged:	
			If a generator is used, is gas and generator transported	
			with samples or sample containers:	

EENTIGUA

If yes, what QA/QC measures are taken to monitor or avoid possible contamination:

		• Who is responsible for pump and power source
		maintenance:
		Is purging equipment operated and maintained properly:
	2.	Is well purged in a way that will insure water and well integrity: Yes Jour Mary minimum Prise
	3.	What type of disposable gloves are being used:
	4,	Are gloves changed when soiled:
	S .	12 Mett Actitisted:
	6.	How is total volume purged measured: Oncharts by outse park the safe to the sa
	7.	How is total volume purged measured:
	8,	Is purge rate recorded:
	9.	Are beginning date and times recorded: How is purge water being handled: See built of the control of the con
	10.	How is purge water being handled: Deal woods of well hooks, the Charles
	4-	distinged to LCS in Card bridges
	11.	Are any wells being purged to dryness:
		a. At what point is the well being called dry: b. Is one (1) to three (3) volumes being purged:
		b. Is one (1) to three (3) volumes being purged:
		c. Is the well being purged more than once before sampling: 1.16
		d. Is the field log noted that the well went dry:
	12.	Are any wells being purged to three (3) yolumes: No low flow for purge
	13.	Are stabilization measurements taken:
		a. If so, which parameters: DTW, pt. Temp, SC, 1-40g-15
		b. Is so, have meters been calibrated on same day:
		c. If so, have meters been checked with standards before starting
		individual well measurements:
	9.4	d. If so, are measurements recorded on stabilization log:
	14. 15.	Is field log maintained at well head: Is water level measured after purge:
	13.	is water level measured after purge:
		•
Com	ments:	
***************************************	<u> </u>	
'D.	SAM	PLING '
		$oldsymbol{arphi}$
	1.	Is water level measured at time of sampling:
	2.	Is date and time of sampling recorded:
	3.	Method used for sampling:

AUDIT/93

'n.

	Analyte order: VX TOC PAD:
	Is bailer lowered and raised to avoid agitation of water:N/A
	Is pump rate acceptable to sample volatile compounds:
	Is water transferred to containers carefully:
	Are samples transferred from sampling device to its compatible containers:
. *	Is care being taken to avoid placing clean sampling equipment and bottles on the ground or other contaminated surface:
	Are samples preserved properly: \(\lambda = pre-pre-pre-pre-pre-pre-pre-pre-pre-pre-
	Are sample containers cleaned according to 1986 TEGD: N/A
	Is well sequence recorded:
	What indicator parameters are being measured in the field:
	Are four (4) replicates being measured for field measurements:
	Are meters calibrated according to manufacturers instructions: 45
	How often are meters checked with standard solution:
	Is standard solution changed daily:
	Are measurements of standard solution recorded on field log: 80 CALIDRALION
	Are meter identification recorded:
	Are meter probes riused with delonized water between wells:
	Are meter probes decontaminated between sites according to manufacturers instructions:
	Have meter batteries been changed within the past six (6) months:
	Are clean, chemically inert gloves being worn throughout sampling process:
	Are weather conditions being recorded:
	Are sample characteristics being recorded:
	Are analyte collection order, sample containers, preservatives, and tests to be performed being recorded:
	Is comment section being utilized: AS Deckel
	Is field log being signed on the same date as the sampling taking place:
	Is field data checked with past field data:

AUDITION

E. HANDLING

	er divi lucatar.		
When were	ed and locked: Yes bottles preserved: Yes brees	meserved by	
Do horda la	ibels contain:		CONTROL OF THE PROPERTY OF THE
a.	Sample I.D. #	You - union	e sende numbre
ъ. b.	Name of collector	Traile &	
c.	Date and time of collection	Control of the Contro	The same of the sa
d.	Place of collection		estella production de la company de la compa
e.	Parameters requested		<u>Ca. Total</u> Pella
A one or or or or	ameters filtered: NA		
a.	How:	FORTING DESCRIPTION AND ASSESSMENT OF THE PROPERTY OF THE PROP	A CONTROL OF THE CONTROL OF THE PROPERTY.
€%.	SALU VI .	·	**************************************
Is non-dedic	cated equipment decontaminated ac	cording to the 1986 1	FGD:
	NIA	•	***************************************
Are sample	s cooled to ≤ 4° C immediately:	Mes -> placed in	THE STORY CONTRACTOR
Are custody	seals placed on individual bordes	of sample shuttle kits	: NO->
	on coolers price to s		
	ent and samples being transported		Riel* A/A
Tilber ess es	otential contaminants of equipment		CANCELLE ST. AND
witer are be	armer conferming or edathmen	i enn semines norm£ c	Tattallarr .
THE TANK PER VIEW		to me and the second of the se	and the state of t
### 1	lls and between site and lab:	h cetap asoci	ush jushich extrais, with
Are field bl	anks used, at least, in a one (1) in	i twenty (20) ratio:	ust valide extraop, etc.
Are field bl Where does	anks used, at least, in a one (1) in i field water come from: <u>Tasal A</u>	twenty (20) ratio: マムルム ショルル (25)	ust valide extraop, etc.
Are field bl Where does Is every pai	anks used, at least, in a one (1) in a field water come from: 1204 Avrancter tested with the field blank	twenty (20) ratio:	preday
Are field bl Where does Is every pai	anks used, at least, in a one (1) in a field water come from: 1204 Avrancter tested with the field blank	twenty (20) ratio:	preday
Are field bl Where does Is every par Are trip bla	anks used, at least, in a one (1) in a field water come from: The Ambarameter rested with the field blank take used, at least, in a one (1) in	twenty (20) ratio:	preday
Are field bl Where does Is every par Are trip bla	anks used, at least, in a one (1) in a field water come from: The hard hard rameter tested with the field blank takes used, at least, in a one (1) in	twenty (20) ratio: twenty (20) ratio:	preday
Are field bl Where does Is every par Are trip bla Is every par	anks used, at least, in a one (1) in a field water come from: The Analogue frameter tested with the field blank tanks used, at least, in a one (1) in the contact of the same frameter tested with the trip blank:	twenty (20) ratio:	Deedoy To pa cooke
Are field bl Where does Is every par Are trip bla Lis every par	anks used, at least, in a one (1) in a field water come from: The hard hard rameter tested with the field blank takes used, at least, in a one (1) in	twenty (20) ratio:	Deedoy To pa cooke
Are field bl Where does Is every pai Are trip bla Is every pai Are duplica	anks used, at least, in a one (1) in a field water come from: The American rested with the field blank take used, at least, in a one (1) in the contact of the trip blank: the samples used, at least, in a one rameter tested with the duplicate:	twenty (20) ratio: twenty (20) ratio: \[\sum_{\infty} \colongright \text{\lambda} \	Deedoy To pa cooke
Are field bl Where does Is every pai Are trip bla Is every pai Are duplica Is every pai	anks used, at least, in a one (1) in a field water come from: The American rested with the field blank take used, at least, in a one (1) in the contact of the trip blank: the samples used, at least, in a one rameter tested with the duplicate:	twenty (20) ratio: twenty (20) ratio: \[\sum_{\infty} \colongright \text{\lambda} \	Deedoy To pa cooke
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank tanks used, at least, in a one (1) in the control of the	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio	to: 1110 miles
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col Are equipm	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank takes used, at least, in a one (1) in trameter tested with the trip blank: the samples used, at least, in a one rameter tested with the duplicate: liected for Matrix spikes: liected for Matrix spikes:	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio	to: 1110 miles
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col Are equipm	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank tanks used, at least, in a one (1) in the rameter tested with the trip blank: the samples used, at least, in a one rameter tested with the duplicate: liected for Matrix spikes: lected for Matrix spikes:	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty	Deedong about the particular and
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col Are equipm	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank takes used, at least, in a one (1) in trameter tested with the trip blank: the samples used, at least, in a one trameter tested with the duplicate: lected for Matrix spikes:	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty	Decade above (20) ratio: In field loss:
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Are duplica Are equipm Are equipm Are field par	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank take used, at least, in a one (1) in trameter tested with the trip blank: the samples used, at least, in a one trameter tested with the duplicate: leet rinsate blanks used, at least, in a comparameters of QA/QC samples, meaning the comparameters of QA/QC samples, meaning th	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty Isured and recorded or	Decode (20) ratio: n field logs:
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col Are equipm Are field par Are all of the	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank takes used, at least, in a one (1) in the samples used, at least, in a one rameter tested with the duplicate: liected for Matrix spikes: liected for Matrix spikes: lent rinsate blanks used, at least, in a one carameters of QA/QC samples, means the parameters affected by non-ded	twenty (20) ratio: twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty sured and recorded on licated equipment teste	Decode (20) ratio: n field logs:
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col Are equipm Are field par Are all of the	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank takes used, at least, in a one (1) in trameter tested with the trip blank: the samples used, at least, in a one trameter tested with the duplicate: liected for Matrix spikes: liected for Matrix spikes: least rinsate blanks used, at least, in a one trameters of QA/QC samples, means the parameters affected by non-dedictinsate blank:	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty sured and recorded one a sured and recorded one content tester than the content tester	io: 1/10 mio: n field logs:
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col Are equipm Are field par Are all of the equipment r Is all non-de	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank tanks used, at least, in a one (1) in trameter tested with the trip blank: the samples used, at least, in a one rameter tested with the duplicate: liected for Matrix spikes: least rinsate blanks used, at least, in a one trameters of QA/QC samples, meaning the parameters affected by non-dedinisate blank: edicated equipment that comes into the samples into the parameters affected by non-dedinisate blank: edicated equipment that comes into the parameters into the parameters affected by non-dedinisate blank:	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty sured and recorded or clared equipment teste contact with the wel	io: 1/10 mio: n field logs:
Are field by Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col Are equipm Are field part all of the equipment is all non-diested with	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank take used, at least, in a one (1) in trameter tested with the trip blank: the samples used, at least, in a one rameter tested with the duplicate: liected for Matrix spikes: lent rinsate blanks used, at least, in a one trameters of QA/QC samples, meaning the parameters affected by non-dedinsate blank: edicated equipment that comes into an equipment rinsate blank:	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty sured and recorded or contact with the well	io: 1110 miles (20) ratio: In field logs: Record with the I water
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Are duplica Are equipm Are field par Are all of the equipment results all non-diested with	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank take used, at least, in a one (1) in trameter tested with the trip blank: the samples used, at least, in a one rameter tested with the duplicate: liected for Matrix spikes: lent rinsate blanks used, at least, in a one trameters of QA/QC samples, meaning the parameters affected by non-dedinsate blank: edicated equipment that comes into an equipment rinsate blank:	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty sured and recorded or contact with the well	io: 1110 miles (20) ratio: In field logs: Record with the I water
Are field by Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col Are equipment and Is all non-diested with Are sample.	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank take used, at least, in a one (1) in trameter tested with the trip blank: the samples used, at least, in a one rameter tested with the duplicate: liected for Matrix spikes: lent rinsate blanks used, at least, in a one trameters of QA/QC samples, meaning the parameters affected by non-dedictions to blank: edicated equipment that comes into an equipment rinsate blank: s packed to avoid breakage, spillages.	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty sured and recorded of the contact with the well contact with the well ge, or cross-contamina	December 2000 (20) ratio: In field logs: Id water Address: 1885
Are field bl Where does Is every par Are trip bla Is every par Are duplica Is every par Is water col Are equipm Are field par Are all of the equipment is all non-ditested with Are sample Is a chain-o	anks used, at least, in a one (1) in a field water come from: rameter tested with the field blank take used, at least, in a one (1) in trameter tested with the trip blank: the samples used, at least, in a one rameter tested with the duplicate: liected for Matrix spikes: lent rinsate blanks used, at least, in a one trameters of QA/QC samples, meaning the parameters affected by non-dedinsate blank: edicated equipment that comes into an equipment rinsate blank:	twenty (20) ratio: twenty (20) ratio: (1) in twenty (20) ratio a one (1) in twenty sured and recorded or licated equipment tester contact with the well ge, or cross-contaminates ample:	December 2000 (20) ratio: In field logs: Id water Address: 1885

AUDIT/93

	b.	Signature of collector:	
	C -	Date and time of collection:	
	đ.	Sample type:	
	€.	I.D. of well: No - > Unique Sanute womber	" Mell IO"
	£.	Number of corrainance	on teleph
	\$.	Parameters requested:	stact w/
	h.	Signatures of persons involved in the chain-of-possession:	Bugg C
	i.	Inclusive dates of possession:	
25.	Is sample ar	Inclusive dates of possession:	
26.		e analysis request document the following:	
	3.	Name of person receiving the sample: Yes -> - Coc	
	b.	Laboratory sample number (if different from field number):	
	C.	Date of sample receipt:	
	d.	Analyses to be performed (including desired analytical method	
		and PQL): on Got of Pole pre-appeared	
	C.	Information that may be useful to the laboratory (e.g. Health	
		and Safety precautions): it needed - comment section or	r Cristian
27.	Is BFI field	log being used: CMI THE BE	
చూరి.			
27. 28.	How are sar	inples being delivered and when: Test Amarkica courties	
		mples being delivered and when: Test a market a countries	

CMI PARAMETE LIST + Continuos:

VOCS - 3×40 ml glass vials w/ septim

TDC - 2 MD ml glass viols of septimer - prepensaged of HCL

PCDs - 2×250 ml ambor oless -unpresserved

AUDIT/93

EXHIBIT NO. 7



520 PECK ROAD DOWNINGTOWN, PA 19335

(610) 873-2691 FAX (610) 873-2692 EMAIL mhadka@trilliuminc.com www.trilliuminc.com

November 19, 2015

Mr. Daniel Deborde Republic Services 5092 Aber Road Williamsburg, OH 45176

RE: Review of Performance Evaluation (PE) and Project Quality Control (QC) Results

Dear Mr. Deborde:

I have completed my evaluation of the PE and QC sample results associated with analyses performed by TestAmerica Buffalo on ground water samples from the Aber Road Landfill site. The samples were collected October 12-13, 2015, and analyzed for volatile organic compounds (VOCs, EPA 8260C), polychlorinated biphenyls (PCBs, EPA 8082A), and total organic carbon (TOC, EPA 9060A). A Level 2 report for TestAmerica Job ID 480-89211 was received by Trillium for review on November 6, 2015. Unless otherwise specified in this report, my review was based on the information contained in this laboratory report.

Performance Evaluation Samples

In lieu of a laboratory audit, three double-blind PE samples for project-specific VOCs were included in the October 2015 sampling and analysis program. The custom PE samples were prepared by ERA in Golden, Colorado, according to specifications provided to them by me, in consultation with Mike Gibson of Eagon & Associates, Inc. Nine 40-mL sample vials containing the custom PE sample preserved with HCl were shipped directly to Andy Graham in Williamsburg, Ohio, for his receipt on October 9, 2015.

To ensure that the PE samples were not identifiable as such by the laboratory, the PE samples were not labeled when shipped from ERA. In the field, the PE samples were given false sampling locations including dates and times of collection on the chain of custody records to appear as though they were samples collected at the site. The nine 40-ml PE samples were split into three samples that were submitted to the laboratory. The sample IDs used for the three PE samples were GW-101215-NK-002, FB-101215-NK-009, and GW-101215-CG-013 (see

HOME OFFICE

28 GRACE'S DRIVE • COATESVILLE, PA 19320 • (610) 383-7233 • FAX (610) 383-7907 OFFICES IN:



Mr. Daniel Deborde November 19, 2015 Page 2 of 6

Attachment A). Labels routinely provided by the laboratory for this project were used on all of the PE sample containers. All of the samples from this sampling event were received by the laboratory on October 15, 2015.

The certified concentrations of the six target analytes included in the PE samples may be found on the Certificate of Analysis provided by ERA and included in Attachment B. Results for all six target analytes in the PE samples were within the acceptance limits established by ERA except for 1,1,1-trichloroethane in GW-101215-CG-013:

	Certified	Measure	Acceptance			
Analyte	Value ug/L	GW-101215- NK-002	FB-101215- NK-009	GW-101215- CG-013	Limits (ug/L)	
Benzene	4.13	3.9	3.8	3.8	3.23 - 4.94	
1,2-Dichloroethane	92.0	92	100*	100*	73.2 - 114	
1,1-Dichloroethene	27.2	32	30	30	18.5 - 36.4	
Cis-1,2- Dichloroethene	3.49	3.3	3.4	3.5	2.74 - 4.28	
1,1,1-Trichloroethane	63.9	71	75	79	45.7 - 78.0	
Trichloroethene	6.24	6.1	6.2	6.3	4.62 - 7.48	

^{*} reported from a 2-fold dilution

The undiluted sample result for 1,1,1-trichloroethane for GW-101215-CG-013 was 79 ug/L which was greater than the upper acceptance limit of 78.0 ug/L set by ERA. The laboratory also reported the results for a 2-fold dilution for this sample in order to dilute the concentration of 1,2-dichloroethane into the calibration range. The result for 1,1,1-trichloroethane for GW-101215-CG-013 run at a 2-fold dilution, 73 ug/L, was within ERA's acceptance limits. Trillium used the undiluted value for 1,1,1-trichloroethane because it was the least dilute analysis of GW-101215-CG-013 within the calibration range.

Compared to the certified values, the spiked analytes had recoveries ranging from 92% to 124%. The 124% recovery result was for 1,1,1-trichloroethane for GW-101215-CG-013. Precision across the triplicate analyses was also very good, with percent relative standard deviations ranging from 2% (benzene and trichloroethene) to 5% (1,1,1-trichloroethane).

Overall, the PE sample results reported by the laboratory demonstrate good accuracy and precision for analysis of these VOCs pursuant to EPA 8260C.



Mr. Daniel Deborde November 19, 2015 Page 3 of 6

Analytical Quality Control Results

Volatile Organics (EPA 8260C)

Based on the summary forms provided in the Level 2 report, no QC issues were encountered during analysis of the site samples for VOCs. Recoveries of all three surrogate compounds (94% to 117%) were within the surrogate-specific acceptance limits in all reported analyses.

Five method blanks and five laboratory control samples were analyzed with the submitted samples. No target analytes were detected in the blanks, and recoveries of the four spiked analytes, 89% to 106%, were within the laboratory-specified, analyte-specific acceptance limits. The four spiked compounds were 1,1-dichloroethene, benzene, chlorobenzene, and trichloroethene.

Two matrix spike/matrix spike duplicate (MS/MSD) pairs were prepared and analyzed with the submitted samples. Reported recoveries of the four reported spiked analytes (1,1dichloroethene, benzene, chlorobenzene, and trichloroethene) were acceptable for both spiked analyses of GW-101315-NK-022 (99% to 116%) and GW-101215-NK-011 (100% to 112%). Excellent reproducibility was demonstrated for the paired measured concentrations, with relative percent differences (RPDs) ranging from 3% to 8%. Note that the laboratory's case narrative states that the recoveries for the MS/MSD for analytical batch 480-270349 were outside the control limits. However, the recoveries for the four reported spiked analytes (1,1-dichloroethene. benzene, chlorobenzene, and trichloroethene) in the MS/MSD for analytical batch 480-270349, which spiked GW-101315-NK-022, had acceptable recoveries (99% to 116%). Additional compounds including 1,1,1-trichloroethane and 1,2-dichloroethane were spiked in GW-101315-NK-022 for the MS/MSD and the results reported in the Target Compound Quantitation Reports (pages 782 to 788) in the Level 4 data package. The MS/MSD recovery for 1,1,1-trichloroethane was 137% and 111% with an RPD of 25% and for 1,2-dichloroethane the recoveries were 128% and 0% with an RPD of 116%. No MS/MSD acceptance limits were given for 1,1,1trichloroethane and 1,2-dichloroethane. The laboratory qualified 1,1,1-trichloroethane and 1,2dichloroethane in sample GW-101315-NK-022 as "F1" meaning "MS and/or MSD recovery is outside the acceptance limits."

Two field blanks, two equipment blanks, and one trip blank were submitted for analysis during this sampling event (see Attachment A). A low concentration of acetone (3.2 J $\mu g/L$) was reported in equipment blank EB-101315-NK-029. Since acetone was not reported in any of the site samples, this blank contamination has no effect on the sample results. Note that the sample ID of one of the field blanks FB-101215-AG-005 was mislabeled as GW-101215-AG-005 on the laboratory forms.

Three field duplicate samples GW-101215-CG-015, GW-101215-NK-019, and GW-101315-AG-032 were submitted for analysis during this sampling event (see Attachment A). GW-101215-CG-015 was the field duplicate of GW-101215-CG-014, GW-101215-NK-019 was



Mr. Daniel Deborde November 19, 2015 Page 4 of 6

the field duplicate of GW-101215-NK-018, and GW-101315-AG-032 was the field duplicate of GW-101315-AG-031. Paired positive results showed acceptable reproducibility (11 RPD and 12 RPD).

The samples were analyzed for volatile organics within 14 days of collection, which is within the method-specified maximum holding time of 14 days from collection for acidified and refrigerated water samples. Note that the date of collection for the PE samples was November 12, 2015 on the chain of custody, however, the sample preparation date by ERA was November 8, 2015. Based on the PE preparation date, the undiluted analysis of the PE samples were all within 14 days of sample preparation. However, the 2-fold dilution of FB-101215-NK-009 and GW-101215-CG-013 was analyzed on day 15 after sample preparation by ERA. Assuming the samples were properly stored prior to analysis, it is unlikely that a one-day delay had a significant effect on the sample results.

Acceptable cooler temperatures (2.1°C to 3.9°C) were documented in the narrative. Acidification of the PE samples with hydrochloric acid (HCl) was documented by ERA (see Attachment B), but no documentation of pH measurements was found in the Level 2 laboratory report. In the Level 4 data package, acceptable pHs of <2 were documented for all of the samples in this data set on the GC/MS VOA Worksheets (pages 803-813).

Polychlorinated Biphenyls (EPA 8082A)

Based on the summary forms provided in the Level 2 report, no QC issues were encountered during analysis of the site samples for PCBs. Recoveries of both surrogate compounds (33% to 114%) were within the laboratory-specified acceptance limits (QC 24-150%) in all reported analyses.

Two method blanks and two laboratory control samples were prepared and analyzed with the submitted samples. No target analytes were detected in either of these blanks. Recoveries of PCB-1016 and PCB-1260 (72% to 87%) in the laboratory control samples were within the laboratory-specified, analyte-specific acceptance limits in both control samples.

Two MS/MSD pairs were prepared and analyzed with the submitted samples. All reported recoveries were acceptable for both spiked analyses of GW-101215-NK-011 (74-95%) and GW-101315-NK-022 (58% to 95%). Acceptable reproducibility was demonstrated for the paired measured concentrations, with RPDs ranging from 2% to 16%.

Two field blanks and two equipment blanks were submitted for analysis during this sampling event. No PCBs were detected in either field blank. Note that the sample ID of one of the field blanks FB-101215-AG-005 was mislabeled as GW-101215-AG-005 on the laboratory forms.

Two field duplicate samples GW-101215-CG-015 and GW-101215-NK-019 were submitted for analysis during this sampling event (see Attachment A). GW-101215-CG-015 was



Mr. Daniel Deborde November 19, 2015 Page 5 of 6

the field duplicate of GW-101215-CG-014 and GW-101215-NK-019 was the field duplicate of GW-101215-NK-018. No PCBs were detected in the samples.

The samples were extracted on 10/21/15 (eight to nine days after collection) and analyzed on 10/22/15 and 10/23/15. Method 8082A does not specify a maximum holding time for collection to extraction; a holding time of 40 days from extraction to analysis is recommended, and was met for these analyses.

Total Organic Carbon (EPA 9060A)

Based on the summary forms provided in the Level 2 report, no QC issues were encountered during analysis of the site samples for TOC.

Three method blanks and three laboratory control samples were prepared and analyzed with the submitted samples. TOC was not detected in the method blank for analysis batch 270968. However, TOC was detected in both method blanks run with analytical batch 270770 at 0.601 J and 0.576 J mg/L. The laboratory qualified all detected results for TOC run in analytical batch 270770 with a "B" indicating "compound was found in the blank and sample." Recoveries of TOC in the laboratory control samples (96% to 102%) were within the laboratory-specified acceptance limits of 85-115%.

Two MS/MSD pairs were prepared and analyzed for TOC with the submitted samples. The reported recoveries were acceptable for both spiked analyses of GW-101215-NK-011 (104% and 106%) and GW-101315-NK-022 (96% and 97%). Excellent reproducibility was demonstrated for both pairs of measurements, with RPDs of 2% and 1%, respectively. Acceptable recoveries, 94% and 91%, were also obtained for the MS prepared and analyzed on GW-101215-NK-018 and EB-101315-NK-029, respectively.

Samples GW-101215-NK-012 and GW-101315-NK-028 were analyzed in duplicate by the laboratory. Paired positive results for TOC showed acceptable reproducibility (6 RPD and 3 RPD) in both cases.

Two field blanks and two equipment blanks were submitted for analysis during this sampling event (Attachment A). No TOC was detected in the field or equipment blanks. Note that the sample ID of one of the field blanks FB-101215-AG-005 was mislabeled as GW-101215-AG-005 on the laboratory forms.

Two field duplicate samples GW-101215-CG-015 and GW-101215-NK-019 were submitted for analysis during this sampling event (see Attachment A). GW-101215-CG-015 was the field duplicate of GW-101215-CG-014 and GW-101215-NK-019 was the field duplicate of GW-101215-NK-018. Paired positive results for TOC showed acceptable reproducibility (1 RPD and 0 RPD) in both cases.



Mr. Daniel Deborde November 19, 2015 Page 6 of 6

Equipment blank EB-101315-NK-029 was prepared as a matrix spike for TOC. It must be noted that QC analyses using equipment blanks provide no useful information for evaluation of site sample results.

This concludes my review of the PE and analytical QC results generated in association with the October 2015 sampling event at Aber Road Landfill. Please let me know if you have any questions.

Regard

Michael C. Hadka, Ph.D.

Chemist

MCH/hrs



Attachment A

Michael Hadka

From: Date: "Mike Gibson" <mgibson@eagon.cc> Thursday, November 12, 2015 4:09 PM

To:

"'Michael Hadka'" <mhadka@trilliuminc.com>

Cc:

"'Daniel Deborde''' <ddeborde@republicservices.com>; "'Joe Montello''' <JMontello@republicservices.com>

Attach:

Oct15 EventSummTbl.pdf

Subject:

RE: CECOS Aber Road October 2015 CMI PE sample results

Michael, The sample ID key for all samples is attached.

Michael T. Gibson, CPG | Senior Hydrogeologist | Eagon & Associates, Inc.

100 West Old Wilson Bridge Road | Suite 115 | Worthington, OH 43085

Tel. 614.888.5760 | Mob. 614.565.0158 | Fax 614.888.5763 | Email mgibson@eagon.cc

From: Mike Gibson [mailto:mgibson@eagon.cc] Sent: Thursday, November 12, 2015 3:55 PM

To: 'Michael Hadka'

Cc: 'Daniel Deborde'; 'Joe Montello'

Subject: RE: CECOS Aber Road October 2015 CMI PE sample results

See below.

Michael T. Gibson, CPG | Senior Hydrogeologist | Eagon & Associates, Inc. 100 West Old Wilson Bridge Road | Suite 115 | Worthington, OH 43085 Tel. 614.888.5760 | Mob. 614.565.0158 | Fax 614.888.5763 | Email mgibson@eagon.cc

From: Michael Hadka [mailto:mhadka@trilliuminc.com]

Sent: Thursday, November 12, 2015 3:42 PM

To: Mike Gibson

Cc: Daniel Deborde; Joe Montello

Subject: Re: CECOS Aber Road October 2015 CMI PE sample results

Thanks. I am working on the report.

I need to confirm the following:

Is FB-101315-AG-020 a field blank? YES

Are EB-101315-NK-021 and EB-101315-NK-029 equipment blanks? YES

Are there any field duplicates that you would like me to look at? The duplicate samples are: GW-101215-CG-015 (Dup of GW-101215-CG-014), GW-101215-NK-019 (Dup of GW -101215-NK-018), & GW-101315-AG-032 (Dup of GW-101315-AG-031)

Michael Hadka

Trillium, Inc.

Phone: 610-873-2691 Fax: 610-873-2692 www.trilliuminc.com

IMPORTANT NOTICE: This e-mail and any attachments may contain confidential or sensitive information which is, or may be, legally privileged or otherwise protected by law from further disclosure. It is intended only for the addressee. If you received this in error or from someone who was not authorized to send it to you, please do not distribute, copy or use it or any attachments. Please

notify the sender immediately by reply e-mail and delete this from your system. Thank you for your cooperation.

From: Mike Gibson

Sent: Friday, November 06, 2015 3:18 PM

To: Mike Hadka

Cc: Daniel Deborde ; Joe Montello

Subject: CECOS Aber Road October 2015 CMI PE sample results

Michael,

Attached is TestAmerica's level 2 report for the October 2015 CMI event. TA also provides a larger level 4 version of the report. Let me know if you need to see that.

The PE samples are GW-101215-NK-002, FB-101215-NK-009, and GW-101215-CG-013. Needless to say, the "FB" result caught the lab's attention. We told them that these were special samples and that to go ahead and report the results.

Let me know if you have any questions.

Thanks,

Mike

Michael T. Gibson, CPG | Senior Hydrogeologist | Eagon & Associates, Inc. 100 West Old Wilson Bridge Road | Suite 115 | Worthington, OH 43085 Tel. 614.888.5760 | Mob. 614.565.0158 | Fax 614.888.5763 | Email mgibson@eagon.cc

OCTOBER 2015 GROUND-WATER MONITORING SUMMARY CORRECTIVE MEASURES IMPLEMENTATION PROGRAM CECOS-ABER ROAD FACILITY

Well/	Sample C	ollected:	Sample	Monitored	Annual Sampling
Underdrain	Date	Time	LD.	Zone	(Fall - 4th Qtr)*
		М	onitoring Wells Outside Slurry W	'all	
MP-207	10/12/15	1510	GW-101215-NK-008	Upper Sand	COI/TCL VOCs, TOC, PCBs
MP-208	10/12/15	1536	GW-101215-NK-010	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
MP-238AR	10/13/15	1021	GW-101315-NK-026	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
MP-241AR	10/13/15	1030	GW-101315-CG-027	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
MP-249B	10/12/15	1447	GW-101215-CG-007	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
MP-275	10/12/15	1223	GW-101215-CG-014	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
MP-276	10/12/15	1621	GW-101215-NK-011	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
MP-299B	10/12/15	1756	GW-101215-CG-016	Upper Sand	COI/TCL VOCs, TOC, PCBs
MP-303B	10/12/15	1659	GW-101215-NK-012	Upper Sand	COL/TCL VOCs, TOC, PCBs
MP-304	10/12/15	1415	GW-101215-CG-004	вті	COLTCL VOCs, TOC, PCBs
MP-304A	10/12/15	1359	GW-101215-NK-006	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
MP-305	10/12/15	1329	GW-101215-NK-001	BTI	COL/TCL VOCs, TOC, PCBs
MP-305A	10/12/15	1259	GW-101215-CG-003	880 Zone Sand	COLTCL VOCs, TOC, PCBs
MP-306A	10/12/15	1743	GW -101215-NK-018	880 Zone Sand	
141 - 50011	10/12/13		Aonitoring Wells Inside Slurry W		COI/TCL VOCs, TOC, PCBs
MP-202	10/13/15	0940			COLTOL MOO. TOO DOD
MP-219A			GW-101315-CG-023	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
	10/13/15	1130	GW-101315-NK-028	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
MP-222B	10/13/15	0843	GW-101315-NK-022	Upper Sand	COI/TCL VOCs, TOC, PCBs
MP-224B	10/13/15	0931	GW-101315-NK-024	Upper Sand	COI/TCL VOCs, TOC, PCBs
MP-246	10/13/15	1301	GW-101315-NK-030	Upper Sand	COI/TCL VOCs, TOC, PCBs
MP-248B	10/12/15	1851	GW-101215-CG-017	880 Zone Sand	COI/TCL VOCs, TOC, PCBs
	Γ		itional Monitoring Well (See Foo	tnote)	T
MP-290B	10/13/15	0934	GW-101315-AG-025	Upper Sand	DMP & COI/TCL VOCs
	I !		Underdrains	1	
U-11	10/13/15	1250	GW-101315-AG-031	-	COLTCL & DMP VOCs, TOC. PCBs
U-12	10/13/15	1314	GW-101315-AG-033		COLTCL & DMP VOCs, TOC, PCBs
	1 1		QA/QC Samples		1
Duplicate - CMI #1	10/12/15	1723	GW-101215-CG-015	**	COL/TCL VOCs, TOC, PCBs
Duplicate - CMI #2	10/12/15	1743	GW-101215-NK-019	**	COI/TCL VOCs, TOC, PCBs
Duplicate - CM1 #3	10/13/15	1250	GW-101315-AG-032	**	COI/TCL VOCs, TOC, PCBs
Equip. Blank - CMI #1	10/13/15	0810	EB-101315-NK-021	**	COI/TCL VOCs, TOC, PCBs
Equip. Blank - CMI #2	10/13/15	1100	EB-101315-NK-029	**	COI/TCL VOCs, TOC, PCBs
Field Blank - CMI #1	10/12/15	1350	FB-101215-AG-005	**	COLTCL VOCs, TOC, PCBs
Field Blank - CMI #2	10/13/15	0845	FB-101315-AG-020	**	COLTCL VOCs, TOC, PCBs
Matrix Spike-CMI #1	10/12/15	1621	GW-101215-NK-011-MS	**	COI/TCL VOCs, TOC, PCBs
Matrix Spike DupCM1#1	10/12/15	1621	GW-101215-NK-011-MSD	**	COUTCL VOCs, TOC, PCBs
Matrix Spike-CM1#2	10/13/15	0843	GW-101315-NK-022-MS	**	COI/TCL VOCs, TOC, PCBs
Matrix Spike DupCMI #2	10/13/15	0843	GW-101315-NK-022-MSD	**	COI/TCL VOCs, TOC, PCBs
Lab Audit Blank (1)	10/12/15	1259	GW-101215-NK-002		COI/TCL VOCs
Lab Audit Blank (2)	10/12/15	1500	FB-101215-NK-009		COI/TCL VOCs
Lab Audit Blank (3)	10/12/15	1617	GW-101215-CG-013		COI/TCL VOCs
Trip Blanks	***	***	***	**	COI/TCL VOCs

^{* -} TOC and PCB samples are collected as part of the TSCA program.

Note: MP-290B is sampled as an additional well per USEPA request to monitor sanitary landfill.

^{** -} Duplicates and equipment and field blanks are collected at a rate of 1 per 10 samples; matrix spikes 1 per 20 samples; and trip blanks at a rate of one per shipment of VOC samples.



Attachment B



A Waters Company

October 9, 2015

Michael Hadka Trillium Inc 520 Peck Road, Downingtown, PA 19355

Dear Michael:

Enclosed please find the certified values for the whole volume double blind performance evaluation samples that were recently ordered by Daniel Deborde. The samples were shipped on October 8, 2015 via FedEx Priority over-night service to Andy Graham in Worthington, OH. The ERA project number corresponding to these samples is 0917-15-01.

Thank you for choosing ERA for this project. If you have any questions or if we can be of any further assistance please do not hesitate to call.

Sincerely.

Chad Lane Chemist

enclosures

cI



COPY

A Waters Company

ERA, A Waters Company Sample Identification and Chain of Custody Form

Sample

Ship to:	Eagon & Associates
	100 Old Wilson Bridge Road

Suite 115

Worthington, OH 43085

Sample

Ship from: ERA, A Waters Company

of

16431 Table Mountain Parkway

Gelden, CO 80403

Phone:

Sample

Fax: Attention: Andy Graham Phone: 800-372-0122 or 303-431-8454

Fax: 303-421-0159 Contact: Chad Lane

Sample |

Description	identification	Date	Type	Containers	Preservative
Volatiles	0917-15-01	10/8/2015	Aqueous	9 x 40 mL	HOI
		ůmij.			
	1			_	
	*	1			
,					
		: Y			
				1	
		<u> </u>			
,					
		-			
					· · · · · · · · · · · · · · · · · · ·
	1			<i>n</i>	
	AND COMMENCES OF		- Lander		Condition of Contents
Redinquistred by:	had h		Date/Time: §	3542m	
Received by.	TO SECURE OF THE PROPERTY OF T		Dale/Time:		
Relinquished by:			Oste/Time:		
Received by:			Date/Time:		
Relinguished by:			Date/Time:		
Received by:	COMMENT OF THE PROPERTY OF THE		Date/Time:		·



Reference Material

Certificate of Analysis

Product

Custom Stendard

Catalog Number:

J23

Lot No:

0917-15-01

Certificate Issue Date:

Dictaber 8, 2016

Expiration Cate:

na

Revision Number:

Onginal

CERTIFICATION

Parameter	Contilled Value '	Uncertainty *	QC Performance Acceptance Limits *			NIST Traceability 4	
	μg/L	₩.		ug/L		SRMM	Recovery %
Banzena	4.13.	2:10	3.23	-6 T., · 1 · · · · · · · · · · · · · · · · ·	4.94	63	na
1,3-Dichloroethane	92.0	1.66	73.2	*	7 14	na	na
1.1-Dichlorositylene	27.7	1,83	18,5	and a	36.4	กร	112
cis-1.2 Dichloroethylens	3 49	161	2.74		4 28	na	na
1,1,1-Trichloroethane	6 3.9	1.74	45.7	, 5:	78.U	na	ha
Trichloroethylene	6.24	2.05	4.62	·	7 48	na	na

Matrix:

18 magchm daionizad water with HCI

Density:

Storage:

432"(

Manufacturing Molos:

The sample is ready for preparation and analysis as received.

- 1. The Codined Values are equal to 100% of the "minds to" values as determined by volumetric analysis gravimatic measurements made builting the manufacture of inia product
- 2 The stated Uncertainty is the total propagated uncertainty at the fistile coalidable treated. This tableted in the preparation and (se noted) intention analytical verification of the product by ERA, multiplied by a coverage factor. The unvertently applies to the product or expedied (and dolph not take talk account any required or optional dilution and/or preparations the laboratory may perform while using this product.
- The Parismance Acceptance Limits (PALSTY) are listed as quidelines for exceptable analytical results given the limitations of the USEPA methodologies. commonly used to determine these parameters and classly approximate the 98% confidence interval. The PALs ** are based on analytical ventication date pergrated by ERA, independent reletive biborately results another data from USEPA methods, WP, V/S and CLP interlaboratory studies. Recovery and advisory range data for these attitles are based on ERA's framel menulantuming ranges. The PALEM listed for this Bentains, class, 2-Dichlerouthylena and Trichtorosthylens may not be applicable since the analyte comparation is outside of ERA's normal manufacturing range and a linear relationship to the concentration listed free not been established. If your neal rest outside of the PALE®, ERA recommends that you investigate potential sources of error in your propuration enclor enalytical procedures. For fiether lecturical assistance, cell ERA at 1-600-872-0122
- 4. Where NIST Standard Reterance Meterials (SRIvia) are aveilable, each enclyle has been analytically fraced to the NIST SRM taked. Traceability Recovery % If is receiving conflict alordered (% recovery NIST SPIM); "NICL The deceasely data shown were completed by analyzing the ERA standards or that associated stack -sclutions against the applicable MST SRMs.

If you have any questions or need iscimical essistance, please call ERA technical assistance at 1-800-372-0122 or sand an email to info@eraqu.com.

Cartifying Officer:

Bin Mill

Brian Miller

Quality Officer: Kristins Senchez

16341 Table Mountain Pkwy - Golden, GO 80403 - T: 800-372 0122 - 303 431 8464 - www.eraqu.com

CD # 1175 50075-3 Rev T 1011

EXHIBIT NO. 8

DAT Reports®

Data Analysis Technologies, Inc.

7715 Corporate Blvd. Plain City, OH 43064 800-733-8644

Sample Analysis Certificate

Client: Address: Eagon & Associates

Suite 320

Columbus, OH

Date:

8/5/2015

DAT Project ID: Date Received:

0715027 7/16/2015

Attn:

Mike Gibson

Client Project: CECOS-Aber Rd (MOVP)

Analysis:

Method 25E

The following samples were received on 7/16/2015:

DAT Sample ID	Client Sample ID	Date Sampled	Matrix
0715027-1	MOVP Influent	7/15/2015	Aqueous
0715027-2	MOVP Influent Duplicate	7/15/2015	Aqueous
0715027-3	MOVP Influent Duplicate Dup	7/15/2015	Aqueous

Results:

See attached summary.

QC:

Met the criteria for the method.

Reviewed and approved for release by:

Ronald K. Mitchum, Ph.D.

President, DAT

DAT Reports®

Data Summary

Method 25E / Organic Vapor Pressure

Client: Client Project: Eagon and Associates

DAT Project:

Cecos Aber Rd. MOVP

Date Sampled:
Date Received:

0715027 7/15/2015

Date Received: Date Analyzed:

7/16/2015 7/30/2015

Analyst: P(bar), in Hg:

SM 30.00

7/30/2015

		Vapor		
Client ID	DAT ID	Temperature, °C	ppm VOC	Pressure, psi
MOVP Influent	0715027-1	24	1835.7	0.027
MOVP Influent duplicate	0715027-2	24	1454.3	0.021
MOVP Influent duplicate dup	0715027-3	24	1334.0	0.020
blank		24	2.44	0.000

P(bar) = Local barometric pressure

ppm = Headspace concentration (v/v) as propane

Vapor Pressure (psi) = $k \times ppm \times P(bar (in Hg))$

 $k = 4.91 \times 10E-7 \text{ psi/[(in Hg) (ppm)]}$

DAT Reports®

QC Summary

Method 25E / Organic Vapor Pressure

Client:

Eagon and Associates

Client Project:

Cecos Aber Rd. MOVP

DAT Project:

0715027

Date Analyzed:

7/30/2015

Analyst:

SM

P(bar), in Hg:

30.00

Sample ID	Concentration	ppm VOC, Run 1	ppm VOC, Run 2	ppm VOC, Run 3	ppm VOC, Avg.	% RSD
Low Standard	1000 ppm	1037	1095	1085	1072	2.9
Mid Standard	5000 ppm	5073	5375	4964	5137	4.1
High Standard	10000 ppm	10165	10024	9567	9919	3.2

% RSD Limit:

5.0 Max



Page

9

SERIAL Nº 29305

ANALYSIS REQUEST AND CHAIN OF CUSTODY RECORD

7715 CORPORATE BLVD. PLAIN CITY, OHIO 43064 614-873-0710 800-733-8644 FAX 614-873-0810

"Analytical Laboratories and Consultants" FAX 614-873-0810 PROJECT REFERENCE PROJECT NO. P.O. NUMBER MATRIX CEOS-Aby Rd (MOVP)
DECTLOC. SAMPLER(S) NAME REQUIRED ANALYSIS PAGE TYPE OF PHONE 614) 888-5760 FAX 888-5763 STANDARD REPORT CLIENT NAME CLIENT PROJECT MANAGER DELIVERY Mike Gibson **EXPEDITED** REPORT 100 W. Od Wilson Bridge Rd., Suite 115, Worthington OH 4308 DELIVERY (SURCHARGE) SAMPLE DATE DUE SAMPLE IDENTIFICATION NO. TIME DATE NUMBER OF CONTAINERS SUBMITTED REMARKS 71,51,5 MOVP Influent 3 14:45 14:45 3 14:45 3 TIME RELINQUISHED BY (SIGNATURE) DATE Chris Gordon 71615 7/16/15 1229 RECEIVED BY (SIGNATURE) TIME DATE LABORATORY USE ONLY CUETOUY INTACT CUSTOWY SEAL NO DAT LOG NO LABOFATORY REMARKS Malle 7-16-15 1226 0715027 YES NO

DAT SAMPLE RECEIVING

7715 Corporate Blvd. Plain City,OH 43064.

Project	Number:	0715027
---------	---------	---------

Date Received:	7/16/2015	Carrier:	Hand Delivery			
Client Name:	Eagon & Associates	Analysis:	Method 25E			
Tracking number:	NA	Package Temp:	10 C on ice			
Custody Seals ?	No	coc. 🗹	check if COC from client			

Sample Information

Client ID	Laboratory ID	Date	Matrix	Container:	Comment:
MOVP Influent	0715027-	7/15/2015	Aqueous	40ml VOA Vials	
	1A/B/C/D/E/F/G/	1	^l Liqu i d	•	
	H/I		1		

Laboratory Receiving Initials
0715027

7/16/2015 12:47:29 PM

= -	AT Labs Inc. le Receipt Rep	ort			
Client/Number: Eggon and Associates / 10391			,	The client has been contacted.	
Custodian Initial: AA Date: 7-16-2015				Yes	No
Secondary Review: Initials: Date:	<u> </u>				
Upon receipt of samples, check if any of the following	g discrepancies hav	ve been	noted	L.	
Discrepancy Type				Specify applicable client ID of	or "all"
COC and samples do not match					
No unique sample identifications					
Samples received outside of the required temp criteria.	Receipt Temp:	10°	_C		
No preservation type was noted	Correction Factor:				
No date of collection stated	Corrected Temp:		_C		
No time of collection stated					
The sample collector was not named					
Sample containers were not appropriate					
Sample labels were destroyed or unreadable					
Samples were received outside of holding time					
There was not enough sample to perform the requested a	nalysis.				
Samples showed sign of damage or contamination.		·			
Aqueous samples for volatile analysis: Headspace?	Y N I	Yes, lis	t samp	ele ID(s) in details:	
Details: Sample pH for nonvolatile aqueous samples and presence or absence of headspace (*Under no circumstances shall VOA vials be opened at time of sample receipt.	Y or N) for VOA aqueous sa	umples shall	be recon	ded at time of sample log-in.	
Other Discrepancies:					
Sample ID Discrepancy				Container Re	turn
				Yes / No Price:	
				Size:	
		••••		Return Spl wt:	

Upon receipt, the samples met all of DAT's acceptance criteria.

0715027

DAT Project #

Site Name: CEOS - Abor Rd. Sample CMI Lendrate Point: Triffment Water-Level Time (2400 Hr. Clock) Per Manyle Manhod. X = On
Water-Level Date (AM DD YY) Water-Level Time (2400 Hr. Clock) Fig. 167 compile Mashon. X = Od X =
Well Elevation Depth to Water (DTW) Groundwater Elevation (ff) (site datum, from TOC)
Total Well Depth (from TOC) Water Column Height (from TOC) (ft) (ft) (well depth - DTW) (ft) (ft) (ft)
Purging and Sampling EquipmentDedicated Purging Device A-Submersible Pump B-Peristaltic Pump B-Peristaltic Pump C-Bladder Pump F-Dippes/Bottle X-Other Purging and Sampling EquipmentDedicated Y or N 0.45 pt or 14 (circle of N 0.45 p
Sampling Device C-Bladder Pump F-Dippen/Bottle X-Other C-Bladder Pump F-Dippen/Bottle Tubing ID (Vol/Ft) A-3/8' ID (22 ml/ft) A-3/8' ID (22 ml/ft) X-Other X-Other
PURGE DATE START PURGE TIME ELAPSED HRS WATER VOL (L:Gel) IN ACTUAL VOL PURGED (PUMP/TURING (MM DD YY) (2400 Hr. Clock) (hrs:min) (PUMP/TURING:WELL CASING) (Liters:Gallons) VOLS PURGE one of each circle one (options)
Time DTW Vol. pH Conductance Temp Turbidity R (2400 Hr Clock) (ft) Purged (L: Gals) (std) (jumbos/cm) (°C) (ntu) (ml/
Seggested range for 3 concec. recidings or Permit/Stat: requirements may be entered in spaces provided above (optional).
SAMPLE DATE SAMPLE TIME VOL PURGED PH CONDUCTANCE TEMP TURBIDITY RAMP (MM DD YY) (2400 Hr. Clock) (L.: Galb) (std) (umhou/em) (°C) (std) (mil/
Sample Appearance: Odor: 5 troos Color: Dark Green Other. Weather Conditions (at sample time): Wind Speed/Direction: Air Temp: -30°F Precipitation: Y Specific Comments (including purge/well volume calculations if required):
Sample collected from influent tank in LTS building; samples collected decenting into sample containers from polypropylene beaker. Samples collected:
Samples collected: MOVP
I certify that sampling procedures were in accordance with applicable EPA, State, and Site protocols:

The second of th

the season of th